SAFETY ORGANIZATIONS

THIS FILTER HAS BEEN FORMALLY RECOGNIZED, CERTIFIED OR APPROVED BY THE LISTED AGENCY. THEREFORE, ALL TEST/REQUIREMENTS SPECIFIED IN THE LATEST REVISION OF THE FOLLOWING AGENCY STANDARDS HAVE BEEN MET:

UL RECOGNIZED: UL 1283 CSA CERTIFIED: CSA C22.2 No. 8 VDE APPROVED: EN 60939-2

OPERATING SPECIFICATIONS

LINE CURRENT/VOLTAGE: 10 AMP, 120/250 VAC

LINE FREQUENCY:

50-60Hz

MAXIMUM LEAKAGE CURRENT, EACH LINE TO GROUND:

2µA

@ 120V 60Hz @ 250V 50Hz

OPERATING AMBIENT TEMP. RANGE: -10°C TO +40°C @ RATED CURRENT, Ir. IN AN AMBIENT, $T_{\mbox{\scriptsize Q}}$, HIGHER THAN 40°C, THE MAXIMUM OPERATING

CURRENT, In, IS AS FOLLOWS:

85 - Ta $I_0 = I_r -$

RELIABILITY SPECIFICATIONS:

STORAGE TEMPERATURE: -40°C TO +85°C HUMIDITY: 21 DAYS @ 40°C 95% RH. CURRENT OVERLOAD TEST: 6 TIMES 1, FOR

CUSTOMER DRAWING CATALOG # 10FH71 ECN# APPRVD DATE 10-023669 PJO B

TEST SPECIFICATIONS:

INDUCTANCE: 4.97 mH NOMINAL

CAPACITANCE: (MEASURED @ IKHz, 0.250VAC MAX., 25°C±1°C)

LINE TO LINE:

0.74 μF±20%

DISCHARGE RESISTOR: 470K ∧

L/G AND L/L I.R.

NO DISCHARGE RESISTOR:

6000M₁ (MIN.) @ 100VDC,

20°C AND 50% RH

RECOMMENDED RECEIVING INSPECTION HIPOT:

LINE TO GROUND: 1500 VAC FOR 1 MINUTE LINE TO LINE: 1450 VDC FOR 1 MINUTE

FILTER APPROVAL:

THE BEST WAY TO SELECT AND QUALIFY A FILTER IS FOR YOUR ENGINEERING TO TEST THE UNIT IN YOUR EQUIPMENT.

