UNCONTROLLED DOCUMENT		PART NUMBER	
		SSP-11CR2UP12	В
CAUTION: STATIC SENSITIVE DEVICE			
FOLLOW PROPER E.S.D. HANDLING PROCEDURES			DATE 19.03
WHEN WORKING WITH THIS PART.			.30.06
Ø5.00 [Ø0.197] (12 PLS.)	ELECTRO-OPTIC PARAMETER PEAK WAVELENG FORWARD VOLT/ E FLUX VIEWING ANGLE EMITTED COLOR	AGE 12.0 14.0 V _f 12 LM V _f =1 60 Zx theta	
	LIMITS OF SAFE PARAMETER PEAK FORWARD STEADY CURREN POWER DISSIPA DERATE FROM 2 OPERATING, STO 50 [0.374]	NT 70 mA \TION 105 mW 25°C -1.2 mW/°C DRAGE TEMP40 TO +80 °C	
"UNLESS OTHERWISE SPECIFED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0,039) REV. PART NUMBER	X,X=±0.5 (±0.020), X,XX=±0.25 (±0.010), X,XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.0 <u>CONFIDENTIAL INFORMATION</u> THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF SUNBRITE LEDS.	286 E. HELEN ROAD	l precision
B SSP-11CR2UP12	EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY SUMBRITE LEDS, THE HRUDER OF THS DOCUMENT SHALL KEEP ALL INFORMATION CONTINUED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THRO PARTIES.	PALATINE, IL 60067-69 PHONE: +1.847.359.2790 FAX: +1.847.359.2867 WEB: www.sunbriteleds.co	0
LED MR16 LAMP, GREEN.	RELIABILITY NDTE DUR MANY YEARS OF EXPERIENCE DATA ACCLIMULATION INDICATE THAT SOLDER HEAT IS A NAJOR CAUSE OF EARLY AND FUTURE FALURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.	DRAWN: CHECKED: APPROVED: DATE: 11. Jc PAGE: 1	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Lumex: SSP-11CR2UP12