




- 1. WIRE INSULATION SEALING RANGE: .070-.115 DIA.
- 2. MATES WITH 208677-1 OR 211068-1.
- 3. TOTAL LENGTH OF MATED CONNECTORS IS LESS THAN 2.50 INCHES.
- 4. THIN MEMBRANE PERMISSIBLE ON SMALL DIAMETER OF WIRE SEALS.
- 5. ROTATION OF CAVITY CIRCUIT KEY FROM PART TO PART IS PERMISSIBLE.

208678-1

PART NUMBER

DO NOT SCALE PRINT. UNLESS SPECIFIED DIMENSIONS IN INCHES TOLERANCES ON: 2 PLC DEC * - 3 PLC DEC * - ANGLES * -		DR 9-6-90 J. GALLUCI BG CHK <i>J. Mullin</i> 1-8-91 APPD <i>K. Beane</i> 1-10-91 APPD <i>J. Ferguson</i> 1/24/91		AMP INCORPORATED Harrisburg, Pa. 17105	
MATERIAL SEE CALLOUT		PRODUCT SPEC -		NAME PLUG, 8 POSITION, STANDARD ECONOSEAL CONNECTOR	
FINISH -		APPLICATION SPEC -		WEIGHT -	
		SIZE B	FSCH NO 00779	DRAWING NO 208678	
		SCALE 2:1	SHEET 1 OF 1		

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[208678-1](#)