

PLUG: WB40PR8
 RECEPTACLE: WB40SD6
 XXXXXXXXXXXX

PLUG

RECEPTACLE

SERIES

WB 2 row, right angle, plug, with mounting ears	WB 2 row, straight, receptacle, with mounting ears
---	--

SIZE

20, 30, 40, 50, 60, 70, 80, 90, 100, 110, 128, 132	20, 30, 40, 50, 60, 70, 80, 90, 100, 110, 128, 132
--	--

CONTACTS

TYPE CONTACTS/TERMINATIONS:
 PR8 Pin, right angle, dip solder, .125"

TYPE CONTACTS/TERMINATIONS:
 SD6 Socket, straight, dip solder, .095"
 SD9 Socket, straight, dip solder, .140"
 SD12 Socket, straight, dip solder, .190"
 SD19 Socket, straight, dip solder, .300"

HARDWARE

STYLE OF HARDWARE: (See WB-9)
 K*_* Integral keying guides, polarized
 KY*_* Stainless steel keying guides, polarized
 JMM 2 stainless steel fixed jackscrews

STYLE OF HARDWARE: (See WB-9)
 K*_* Integral keying guides, polarized
 KY*_* Stainless steel keying guides, polarized
 JTFF 2 stainless steel turning jacksockets

DIMENSIONS					
SIZE	A	B	C	D	E
20	1.150	.900	.450	1.030	.750
30	1.400	1.150	.700	1.280	1.000
40	1.650	1.400	.950	1.530	1.250
50	1.900	1.650	1.200	1.780	1.500
60	2.150	1.900	1.450	2.030	1.750
70	2.400	2.150	1.700	2.280	2.000
80	2.650	2.400	1.950	2.530	2.250
90	2.900	2.650	2.200	2.780	2.500
100	3.150	2.900	2.450	3.030	2.750
110	3.400	3.150	2.700	3.280	3.000
128	3.850	3.600	3.150	3.730	3.450
132	3.950	3.700	3.250	3.830	3.550

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[AirBorn:](#)

[M55302/66-56H](#) [M55302/66-50H](#) [WRTA14SECJTH](#) [WB128SD9/12](#)