

LARISA-M-CLIP16

~30° medium beam. Clip fastening for 1.6 mm thick PCB.

TECHNICAL SPECIFICATIONS:

Dimensions	9.9 mm
Height	7.5 mm
Fastening	clips
ROHS compliant	yes ⓘ


MATERIAL SPECIFICATIONS:

Component	Type	Material	Colour	Finish
LARISA-M	Single lens	PMMA	clear	
LARISA-HOLDER-CLIP16	Holder	PC	black	

ORDERING INFORMATION:

Component		Qty in box	MOQ	MPQ	Box weight (kg)
CP12941_LARISA-M-CLIP16	Single lens	10000	300	100	6.6
» Box size: 300 x 250 x 250 mm					









PHOTOMETRIC DATA (MEASURED):





LED XB-D
FWHM 30.0°
Efficiency 84 %
Peak intensity 2.3 cd/Im
LEDs/each optic 1
Light colour White
Required components:





LED XD16
FWHM 27.0°
Efficiency 74 %
Peak intensity 2.2 cd/Im
LEDs/each optic 1
Light colour White
Required components:



LED XP-G
FWHM 36.0°
Efficiency 88 %
Peak intensity 1.9 cd/Im
LEDs/each optic 1
Light colour White
Required components:





LED XQ-E HD
FWHM 25.0°
Efficiency 86 %
Peak intensity 3 cd/Im
LEDs/each optic 1
Light colour White
Required components:




PHOTOMETRIC DATA (MEASURED):





LED XQ-E HI
FWHM 19.0°
Efficiency 79 %
Peak intensity 3.6 cd/Im
LEDs/each optic 1
Light colour White
Required components:





LED H35B0 (LEMWA32)
FWHM 31.0°
Efficiency 89 %
Peak intensity 2.4 cd/Im
LEDs/each optic 1
Light colour White
Required components:



LED H35C0 (LEMWA33)
FWHM 37.0°
Efficiency 87 %
Peak intensity 1.8 cd/Im
LEDs/each optic 1
Light colour White
Required components:





LED LUXEON A
FWHM 37.0°
Efficiency 86 %
Peak intensity 1.7 cd/Im
LEDs/each optic 1
Light colour White
Required components:



PHOTOMETRIC DATA (MEASURED):



LUMILEDS

LED LUXEON C
FWHM 27.0°
Efficiency 85 %
Peak intensity 2.9 cd/lm
LEDs/each optic 1
Light colour White
Required components:





LUMILEDS

LED LUXEON Rebel
FWHM 26.0°
Efficiency 88 %
Peak intensity 3 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LUMILEDS

LED LUXEON Rebel ES
FWHM 35.0°
Efficiency 87 %
Peak intensity 1.9 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LUMILEDS



LED LUXEON Z
FWHM 19.0°
Efficiency 84 %
Peak intensity 5 cd/lm
LEDs/each optic 1
Light colour White
Required components:





PHOTOMETRIC DATA (MEASURED):





LED LUXEON Z ES
 FWHM 24.0°
 Efficiency 88 %
 Peak intensity 3.3 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:





LED NCSxx19A
 FWHM 27.0°
 Efficiency 84 %
 Peak intensity 2.5 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



LED NVSxx19A
 FWHM 34.0°
 Efficiency 84 %
 Peak intensity 1.9 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:





LED Duris S5 (2 chip)
 FWHM 34.0°
 Efficiency 80 %
 Peak intensity 1.9 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



PHOTOMETRIC DATA (MEASURED):



OSRAM
Opto Semiconductors

LED OSLON Square EC
FWHM 31.0°
Efficiency 83 %
Peak intensity 2 cd/lm
LEDs/each optic 1
Light colour White
Required components:





OSRAM
Opto Semiconductors

LED OSLON SSL 150
FWHM 30.0°
Efficiency 88 %
Peak intensity 2.6 cd/lm
LEDs/each optic 1
Light colour White
Required components:



OSRAM
Opto Semiconductors


LED OSLON SSL 80
FWHM 25.0°
Efficiency 82 %
Peak intensity 2.9 cd/lm
LEDs/each optic 1
Light colour White
Required components:



PHOTOMETRIC DATA (SIMULATED):



LED XP-E
FWHM 23.0°
Efficiency 94 %
LEDs/each optic 1
Light colour White
Required components:



GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Salu, Finland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Ledil:

[CP12941_LARISA-M-CLIP16](#)