



注記

- △ □面から2mmの範囲で測定
- 嵌合相手ハウジング型 179679, 179680, 179681
- 適用製品規格番号: 108-5441
- 推奨取付ねじ: JIS B1115, B1122 タップねじ, なべ2種  
呼び径3, 長さ6mm以下 (締付けトルク: 0.4N.m (4Kg-cm) 以下)

NOTES

- △ MUST BE KEPT BETWEEN □ AND 2
- THE MATING PLUG HSG. PART NUMBER; 179679, 179680, 179681
- APPLICABLE PRODUCT SPEC NO. 108-5441
- RECOMMENDED MOUNTING SCREW; 3mm DIA, 6mm LENGTH (MAX.)  
PAN HEAD, CLASS 2 TAPPING SCREW SPECIFIED IN JIS B1115, B1122  
(TIGHTENING TORQUE; 0.4N.m (4Kg-cm) MAX.)

Copyright ©1996 AMP (Japan) LTD. ALL RIGHTS RESERVED.		Copyright ©1996 AMP (Japan) LTD. ALL RIGHTS RESERVED.		GRAY 灰色	900429-6
HOUSING COLOR ハウジング色		AMP		P/N	
材料 (MATERIAL) ハウジング: PBT コンタクト: BRASS		仕上 (FINISH) PRE-TIN 錫メッキ		名称 (NAME) 88Pos. CAP HOUSING ASS'Y .040II/.070II HD HYBRID 1/0 CONN 88極 キャップハウジングアッセンブリ .040II/.070II HD ハイブリット1/0コネクタ	
A 変更 FJ00-0598-98 DM HT 7/30/96	O 作成 FJ00-5121-96 YK KO 7/30/96	DR. Y. KAKITANI 7/30/96	DE. Y. KAKITANI 7/30/96	一般公差 (GENERAL TOLERANCE) 10mm以下: ±0.2 10mm以上, 30mm以下: ±0.25 30mm以上, 100mm以下: ±0.3 角 度: ±3°	LOC 番号 (No.) C J C-900429
LTR 変更 (REVISION RECORD)	DR CHK DATE	CHK. K. ODA	APP. K. ODA	尺度 (SCALE) 1-1	REV. A SHEET 1 OF 1

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[900429-6](#)