

## Coaxial Cable Connector 24\_QMA-50-2-3/133\_N

### Description

Straight bulkhead cable feed through

Interface standards  
QMA QLF compliant



### Technical Data

#### Electrical Data

|                          |       |
|--------------------------|-------|
| Impedance                | 50 Ω  |
| Interface frequency max. | 6 GHz |

#### Mechanical Data

|                |           |
|----------------|-----------|
| Centre contact | soldered  |
| Outer contact  | crimped   |
| Weight         | 0.0043 kg |

#### Environmental Data

|                       |                 |
|-----------------------|-----------------|
| Operating temperature | -40 °C to 85 °C |
| 2011/65/EU, RoHS      | compliant       |

#### Material Data

| Piece Parts    | Material               | Surface Plating       |
|----------------|------------------------|-----------------------|
| Centre contact | Copper Beryllium Alloy | SUCOPRO Plating       |
| Outer contact  | Brass                  | SUCOPLATE (R) Plating |
| Body           | Brass                  | SUCOPLATE (R) Plating |
| Insulator      | PFA / PTFE             |                       |
| Gasket         | VMQ (Silicone rubber)  |                       |
| Fastening nut  | Brass                  | SUCOPLATE (R) Plating |
| Washer         | Bronze                 | SUCOPLATE (R) Plating |
| Crimp ferrule  | Copper                 | SUCOPLATE (R) Plating |

### Related Documents

|                      |                |
|----------------------|----------------|
| Outline drawing      | DOU-00009505   |
| Catalogue drawing    | DCA-00008995   |
| Assembly instruction | DOC-0000179456 |
| Mounting hole        | DOU-00008748   |

### Ordering Information

|                      |                      |
|----------------------|----------------------|
| Single package       | 24_QMA-50-2-3/133_NE |
| Bulk 100 pcs package | 24_QMA-50-2-3/133_NH |

### Additional Information

|                 |                                                  |
|-----------------|--------------------------------------------------|
| Suitable cables | RG_316_/U, ENVIROFLEX_316, RG_188_A/U, RG_174_/U |
|-----------------|--------------------------------------------------|

### Remarks

Chassis torque 2 Nm

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

HUBER+SUHNER:

[24\\_QMA-50-2-3/133\\_NE](#) [24\\_QMA-50-2-3/133\\_NH](#)