

f	0	0	0	0	0	0	0	0	0	0				0	0	0	0	0	0	0	0	0	0
e	6	4	4	4	4	4	4	4	4	6				6	6	4	4	4	4	4	4	4	4
d	6	4	4	4	4	4	4	4	4	6				6	6	4	4	4	4	4	4	4	4
c	6	4	4	4	4	4	4	4	4	6				6	6	4	4	4	4	4	4	4	4
b	5	4	4	4	4	4	4	4	4	5				5	5	4	4	4	4	4	4	4	4
a	6	4	4	4	4	4	4	4	4	6				6	6	4	4	4	4	4	4	4	4
z	0	0	0	0	0	0	0	0	0	0				0	0	0	0	0	0	0	0	0	0
POS	0	0				1				1				2				2					
S	1	5				0				5				0				5					

SEATING PLANE
FOR CONNECTOR

4

8.20

3.70

5

9.70

3.70

6

11.20



3.70

Detailed description: This technical drawing illustrates three different connector types, labeled 4, 5, and 6, positioned vertically relative to a common 'SEATING PLANE FOR CONNECTOR'. Each connector is shown in profile, with a central circular feature. Dimension lines indicate the length of the connector body and the distance from the seating plane to the end of the body. Connector 4 has a body length of 8.20 and a distance of 3.70 from the seating plane to the end. Connector 5 has a body length of 9.70 and a distance of 3.70 from the seating plane to the end. Connector 6 has a body length of 11.20 and a distance of 3.70 from the seating plane to the end.

Technical drawing of a reinforced concrete slab cross-section. The slab is 8.00m wide and 2.00m high. It features a grid of reinforcement bars with a diameter of 2.00mm, tolerance +0.05/-0.05. The drawing shows a cross-section with dimensions: 20.00m total length, 8.00m central section, and 2.00m end sections. Reinforcement bars are spaced at 4.00m and 2.00m intervals. A callout points to a specific bar.

1. THIS PRODUCT IS CSA APPROVED.
2. THIS PRODUCT IS UL RECOGNIZED.
3. MEASURED AT THE BOTTOM.
4. MATERIAL CONTACT: PHOSPHORBRONZE
HOUSING: CREAM WHITE GLASS FILLED POLYESTER UL-94V0
5. CONNECTOR PRINTED WITH P/N AND DATE CODE.
6. FOR ACTUAL CONTACT LOADINGS, SEE LOADING PATTERN MATING SIDE.
7. SHAPE OF CONNECTOR HOUSING CAN ALTER DEPENDING ON
PRODUCTION LOCATION
8. THE PRODUCT (LF) MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY
REGULATIONS AS DESCRIBED IN GS-22-008
9. FOR RECOMMENDED PTH DIMENSIONS REFER DRAWING : BS, A , 201572 , 001

CATALOG NO: HM2P07PDE3F0----

mat'l. code SEE NOTE 4				surface ISO 1302 ✓		tolerance ISO 406 ISO 1101		projection 		product family MILLIPACS													
ltr		ecn no		dr		date		tolerances unless		otherwise specified				title MPACS 5+2R STR HDR PF CONN TYPE A									
A		I04-0058		MINI		2004/10/16		angles linear		.0±0.2													
B		I05-0188		MINI		2005/10/13				.00±0.1													
C		I06-0090		MINI		2006/06/27		0°±1°															
								dr		MINI K VANDANATH		2004/10/16		dwg no sheet 1 of 1 BS, C ,203028, 139 type Product Customer Drawing									
								engr		BUJU K PAUL		2004/10/16											
								chr		BUJU K PAUL		2006/06/27											
								appd		BUJU K PAUL		2006/06/27											
sheet index		revision		C										size A3									
		sheet		1																			

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[FCI / Amphenol:](#)

[HM2P07PDE3F0N9](#) [HM2P07PDE3F0N9LF](#)