



①	Length	Feet	mm	tolerance (mm)	③
001	1	305	+30.5/-15.3		
003	3	914	+45.8/-36.6		
005	5	1524	±45.8		
007	7	2134	±64.1		
010	10	3048	±91.5		
015	15	4572	±137.3		
020	20	6096	±183		
025	25	7620	±228.8		
050	50	15240	±457.5		
100	100	30480	±915		

**SPECIFICATIONS:**

1. CONDUCTORS:
  - 1.1 CONDUCTORS: 24AWG 7\*0.19 ± 0.015mm
  - 1.2 CONDUCTOR INSULATION COLOR CODING: ONE WHITE/ORANGE, ONE ORANGE, ONE WHITE/GREEN, ONE GREEN, ONE BLUE, ONE WHITE/BLUE, ONE WHITE/BROWN, ONE BROWN.
2. CABLE JACKET
  - 2.1 PRINTING ON THE JACKET: CM (UL) C(UL) 4P 24AWG UTP CAT.5E PATCH CABLE ISO/IEC 11801 & EN 50288 & ANS/TIA-568-C.2
3. CABLE ASSEMBLY
  - 3.1 SEE SECTION A-A FOR DIMENSIONS
  - 3.2 CABLE TIE: WHITE TIE
  - 3.3 WIRING T568B COLOR
  - 3.4 CONTACT PLUG: RJ45 8P8C 3u DC UL 94V-2
4. CABLE JACKET COLOR: ACCORDING TO CUSTOMERS REQUEST
5. Dielectric strength: 2.5KV dc-2seconds
6. Working temperatures: -20~60° c

DK-1511-XXXXXX

color:  
BL(black), WH(white), B(blue), G(grey)

Length: see table ①

**ROHS compliant**  
Unit: mm

Scale	Free													
TOLERANCE														
X.	±X	③	Add tolerance for cable length	20.09.2019	Amy	Drawn	24.06.2014	Joanna	ASSMANN WSW-No.	DK-1511-XXXXXX	Customer-No.			
X.XX		②	Add new length version	06.04.2017	Amy	Approved	20.09.2019	Amy						
DIM	TOL	①	Update length version	07.12.2016	Amy				Drawing-No.	ASS 7160 CA			rev03	
X.°		①	Drawn	24.06.2014	Joanna				Replace				SHEET	
Angle	TOL		Id.	Modification	Date	Name								

1	2	3	4	5	6	7
---	---	---	---	---	---	---

A	B	C	D	E	F	G	H
---	---	---	---	---	---	---	---