



LOC	DIST	REVISIONS					
AD	39	P	LTR	DESCRIPTION	DATE	DWN	APVD
			A1	REVISED PER ECO-11-004820	11MAR11	RK	HMR



RECOMMENDED HOLE LAYOUT

1. ASSEMBLY MAY BE BROKEN TO THE DESIRED NUMBER OF POSITIONS
2. TRUE POSITION TOLERANCE OF THE POST TIPS APPLIES WHEN THE HEADER IS HELD FLAT AGAINST THE PRINTED CIRCUIT BOARD
3. THE NOTED DIMENSIONS APPLY AT THE INTERSECTION OF THE POST AND HOUSING
4. HOUSING: FLAME RETARDANT THERMOPLASTIC; COLOR: BLACK.
5. FINISH: 0.00254-0.00508 [.000100-.000200] BRIGHT TIN-LEAD OVER 0.00127 [.000050] NICKEL ENTIRE POST.
6. FINISH: 0.00254-0.00508 [.000100-.000200] MATTE TIN OVER 0.00127 [.000050] NICKEL ENTIRE POST.

6	101.19 [3.984]	99.06 [3.900]	39	40	9-146480-0
6	98.65 [3.884]	96.52 [3.800]	38	39	8-146480-9
6	96.11 [3.784]	93.98 [3.700]	37	38	8-146480-8
6	93.57 [3.684]	91.44 [3.600]	36	37	8-146480-7
6	91.03 [3.584]	88.90 [3.500]	35	36	8-146480-6
6	88.49 [3.484]	86.36 [3.400]	34	35	8-146480-5
6	85.95 [3.384]	83.82 [3.300]	33	34	8-146480-4
6	83.41 [3.284]	81.28 [3.200]	32	33	8-146480-3
6	80.87 [3.184]	78.74 [3.100]	31	32	8-146480-2
6	78.33 [3.084]	76.20 [3.000]	30	31	8-146480-1
6	75.79 [2.984]	73.66 [2.900]	29	30	8-146480-0
6	73.25 [2.884]	71.12 [2.800]	28	29	7-146480-9
6	70.71 [2.784]	68.58 [2.700]	27	28	7-146480-8
6	68.17 [2.684]	66.04 [2.600]	26	27	7-146480-7
6	65.63 [2.584]	63.50 [2.500]	25	26	7-146480-6
6	63.09 [2.484]	60.96 [2.400]	24	25	7-146480-5
6	60.55 [2.384]	58.42 [2.300]	23	24	7-146480-4
6	58.01 [2.284]	55.88 [2.200]	22	23	7-146480-3
6	55.47 [2.184]	53.34 [2.100]	21	22	7-146480-2
6	52.93 [2.084]	50.80 [2.000]	20	21	7-146480-1
6	50.39 [1.984]	48.26 [1.900]	19	20	7-146480-0
6	47.85 [1.884]	45.72 [1.800]	18	19	6-146480-9
6	45.31 [1.784]	43.18 [1.700]	17	18	6-146480-8
6	42.77 [1.684]	40.64 [1.600]	16	17	6-146480-7
6	40.23 [1.584]	38.10 [1.500]	15	16	6-146480-6
6	37.69 [1.484]	35.56 [1.400]	14	15	6-146480-5
6	35.15 [1.384]	33.02 [1.300]	13	14	6-146480-4
6	32.61 [1.284]	30.48 [1.200]	12	13	6-146480-3
6	30.07 [1.184]	27.94 [1.100]	11	12	6-146480-2
6	27.53 [1.084]	25.40 [1.000]	10	11	6-146480-1
6	24.99 [.984]	22.86 [.900]	9	10	6-146480-0
6	22.45 [.884]	20.32 [.800]	8	9	5-146480-9
6	19.91 [.784]	17.78 [.700]	7	8	5-146480-8
6	17.37 [.684]	15.24 [.600]	6	7	5-146480-7
6	14.83 [.584]	12.70 [.500]	5	6	5-146480-6
6	12.29 [.484]	10.16 [.400]	4	5	5-146480-5
6	9.75 [.384]	7.62 [.300]	3	4	5-146480-4
6	7.21 [.284]	5.08 [.200]	2	3	5-146480-3
6	4.67 [.184]	2.54 [.100]	1	2	5-146480-2
6	2.13 [.084]	-	-	1	5-146480-1
PLATING	G	F	E	NO. OF POSITIONS	PART NUMBER

5	101.19 [3.984]	99.06 [3.900]	39	40	4-146480-0
5	98.65 [3.884]	96.52 [3.800]	38	39	3-146480-9
5	96.11 [3.784]	93.98 [3.700]	37	38	3-146480-8
5	93.57 [3.684]	91.44 [3.600]	36	37	3-146480-7
5	91.03 [3.584]	88.90 [3.500]	35	36	3-146480-6
5	88.49 [3.484]	86.36 [3.400]	34	35	3-146480-5
5	85.95 [3.384]	83.82 [3.300]	33	34	3-146480-4
5	83.41 [3.284]	81.28 [3.200]	32	33	3-146480-3
5	80.87 [3.184]	78.74 [3.100]	31	32	3-146480-2
5	78.33 [3.084]	76.20 [3.000]	30	31	3-146480-1
5	75.79 [2.984]	73.66 [2.900]	29	30	3-146480-0
5	73.25 [2.884]	71.12 [2.800]	28	29	2-146480-9
5	70.71 [2.784]	68.58 [2.700]	27	28	2-146480-8
5	68.17 [2.684]	66.04 [2.600]	26	27	2-146480-7
5	65.63 [2.584]	63.50 [2.500]	25	26	2-146480-6
5	63.09 [2.484]	60.96 [2.400]	24	25	2-146480-5
5	60.55 [2.384]	58.42 [2.300]	23	24	2-146480-4
5	58.01 [2.284]	55.88 [2.200]	22	23	2-146480-3
5	55.47 [2.184]	53.34 [2.100]	21	22	2-146480-2
5	52.93 [2.084]	50.80 [2.000]	20	21	2-146480-1
5	50.39 [1.984]	48.26 [1.900]	19	20	2-146480-0
5	47.85 [1.884]	45.72 [1.800]	18	19	1-146480-9
5	45.31 [1.784]	43.18 [1.700]	17	18	1-146480-8
5	42.77 [1.684]	40.64 [1.600]	16	17	1-146480-7
5	40.23 [1.584]	38.10 [1.500]	15	16	1-146480-6
5	37.69 [1.484]	35.56 [1.400]	14	15	1-146480-5
5	35.15 [1.384]	33.02 [1.300]	13	14	1-146480-4
5	32.61 [1.284]	30.48 [1.200]	12	13	1-146480-3
5	30.07 [1.184]	27.94 [1.100]	11	12	1-146480-2
5	27.53 [1.084]	25.40 [1.000]	10	11	1-146480-1
5	24.99 [.984]	22.86 [.900]	9	10	1-146480-0
5	22.45 [.884]	20.32 [.800]	8	9	146480-9
5	19.91 [.784]	17.78 [.700]	7	8	146480-8
5	17.37 [.684]	15.24 [.600]	6	7	146480-7
5	14.83 [.584]	12.70 [.500]	5	6	146480-6
5	12.29 [.484]	10.16 [.400]	4	5	146480-5
5	9.75 [.384]	7.62 [.300]	3	4	146480-4
5	7.21 [.284]	5.08 [.200]	2	3	146480-3
5	4.67 [.184]	2.54 [.100]	1	2	146480-2
5	2.13 [.084]	-	-	1	146480-1
PLATING	G	F	E	NO. OF POSITIONS	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN: E. BRANDBERG 14-MAR--97		 TE Connectivity	
		CHK: G. DUBNICZKI 14-MAR--97			
DIMENSIONS: mm [INCHES]		TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLOC ± — 2 PLOC ± — 4 PLOC ± 0.51[.02] 6 PLOC ± 0.127[.005] 8 PLOC ± 0.127[.005] ANGLES ± — FINISH SEE TABLE		NAME RPO: G. DUBNICZKI PRODUCT SPEC	
		APPLICATION SPEC		HEADER ASSEMBLY, MOD II, STACKING, SINGLE ROW, .025 SO. POST, UNSHROUDED	
MATERIAL: 		WEIGHT —		SIZE A1	
		CUSTOMER DRAWING		CASE CODE 00779	
				DRAWING NO C=146480	
				RESTRICTED TO —	
				SCALE 4:1 SHEET 1 OF 1 REV A1	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[5-146480-7](#)