



Product: [1504A](#) 

Audio Cable, #22-2pr, TC, O/A Foil, CM



Product Description

Audio Cable, CM-Rated, 2-22 AWG stranded tinned copper pairs with PVC insulation, Beldfoil® shield, drain, PVC jacket, parallel construction

Technical Specifications

Product Overview

Suitable Applications:	for use with automatic stripping equipments; low voltage analog signals (4-20ma, 0-10v, ...); low voltage digital control (24v, ...); stereo audio; computer communication; panel wiring
------------------------	--

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	Nominal Diameter	No. of Pairs
22	19x34	TC - Tinned Copper	0.030 in	2

Conductor Count:	4
Total Number of Pairs:	2

Insulation

Material	Nominal Diameter	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.050 in	0.01 in

Color Chart

Number	Color
1	Black & Red
2	Black & Red

Outer Shield Material

Type	Material	Material Trade Name	Coverage [%]	Drainwire Material	Drainwire Diameter	Drainwire AWG	Drainwire Construction n x D
Tape	Alum / Poly	Beldfoil®	100 %	TC - Tinned Copper	0.024 in	24	7x30

Outer Jacket Material

Material	Nominal Diameter	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.286 in	0.020 in

Electrical Characteristics

Conductor DCR

Nominal Conductor DCR	Nominal Conductor DCR	Conductor Resistance	Nominal Outer Shield DCR
13.7 Ohm/1000ft	13.7 Ohm/1000ft		18 Ohm/1000ft

Capacitance

Nom. Capacitance Conductor to Conductor	Nom. Capacitance Conductor to Other Conductor to Shield
57 pF/ft	100 pF/ft

Inductance

Nominal Inductance
0.18 µH/ft

Impedance

Nominal Characteristic Impedance

45 Ohm

Delay

Nominal Delay

1.5 ns/ft

Nominal Velocity of Propagation (VP) [%]

66 %

Current

Max. Recommended Current [A]

2.9 Amps per conductor @ 25°C

Voltage

UL Voltage Rating

150 V RMS

Temperature Range

UL Temp Rating: 60°C

Operating Temp Range: -30°C To +60°C

Mechanical Characteristics

Bulk Cable Weight: 30 lbs/1000ft

Max Recommended Pulling Tension: 25 lbs

Min Bend Radius/Minor Axis: 1.5 in

Standards

NEC/(UL) Specification: CM

CEC/C(UL) Specification: CM

CPR Euroclass: Eca

Applicable Environmental and Other Programs

Environmental Space: Indoor (Not Riser or Plenum)

EU Directive 2000/53/EC (ELV): Yes

EU Directive 2003/11/EC (BFR): Yes

EU Directive 2011/65/EU (ROHS II): Yes

EU Directive 2012/19/EU (WEEE): Yes

EU Directive 2015/863/EU: Yes

EU Directive Compliance: EU Directive 2003/11/EC (BFR)

EU CE Mark: Yes

EU RoHS Compliance Date (yyyy-mm-dd): 2005-10-01

MII Order #39 (China RoHS): Yes

Suitability

Suitability - Indoor: Yes

Flammability, LSOH, Toxicity Testing

UL Flammability: UL1685 UL Loading

ISO/IEC Flammability: IEC 60332-1-2

UL voltage rating: 150 V RMS

Plenum/Non-Plenum

Plenum (Y/N): No

Part Number

Variants

Item #	Color	Putup Type	Length	UPC
1504A J77U1000	Black and Red Pair	UnReel	1,000 ft	612825116165
1504A 0531000	Red and Gray Pair	Reel	1,000 ft	612825116189
1504A 053U1000	Red and Gray Pair	UnReel	1,000 ft	612825116172

1504A 0532000	Red and Gray Pair	Reel	2,000 ft	612825116196
1504A A5QU1000	Red and Green Pair	UnReel	1,000 ft	612825116134
1504A A5Q2000	Red and Green Pair	Reel	2,000 ft	612825116141
1504A G04U1000	Red and Purple Pair	UnReel	1,000 ft	612825116158

Footnote: C - CRATE REEL PUT-UP.

Product Notes

Notes: Overall Nominal Diameter: 0.143 x 0.286 in. The jacket and shield are bonded so both can be removed on automatic stripping equipment. Drain wire is inside foil shield.

History

Update and Revision: Revision Number: 0.255 Revision Date: 04-28-2020

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Belden Wire & Cable:

[1504A J77U1000](#) [1504A A5QU1000](#) [1504A A5Q2000](#) [1504A G04U1000](#) [1504A 0532000](#)