

Feed-through header - MSTBW 2,5/ 5-GF-5,086,03HTBKAU - 1715497

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



PCB headers, nominal current: 12 A, number of positions: 5, pitch: 5.08 mm, color: black, contact surface: Gold

The figure shows a 5-pos. version of the product

Your advantages

- Maximum flexibility when it comes to device design one header for connectors with different connection technologies
- ☑ Well-known mounting principle allows worldwide use
- ☑ Stand-offs enable the PCB to be cleaned or sealed



Key Commercial Data

Packing unit	50 pc
Minimum order quantity	50 pc
GTIN	4 046356 103527
GTIN	4046356103527

Technical data

Dimensions

Pitch	5.08 mm
Dimension a	20.32 mm
Height	15 mm
Length of the solder pin	3.5 mm

General

Range of articles	MSTBW 2,5/GF(6,03)
Rated voltage (III/3)	250 V
Connection in acc. with standard	EN-VDE
Nominal current I _N	12 A
Color	black



Feed-through header - MSTBW 2,5/ 5-GF-5,086,03HTBKAU - 1715497

Technical data

General

Number of positions	5		
Standards and Regulations			
Connection in acc. with standard	EN-VDE		
Environmental Product Compliance			
REACh SVHC	Lead 7439-92-1		
China RoHS	Environmentally Friendly Use Period = 50		
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"		

Approvals

Approvals

Approvals		
EAC		
Ex Approvals		

Approval details

Г

EAC	EAC	B.01742

Phoenix Contact 2018 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany Tel. +49 5235 300 Fax +49 5235 3 41200 http://www.phoenixcontact.com

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Phoenix Contact: 1715497