SC3316FH

SMD POWER INDUCTORS



● Features
1. Open frame construction
2 Excellent Power Density
3 Engineered to Provide High Efficiency

ELECTRICAL CHARACTERISTICS

Part Number	Inductance (uH) (1)	Test Frequency	DC Resistance (Ω MAX) (2)	Saturation Current (3) (A)	Temperature Current (4) (A)
SC3316FH-R27	0.27	100KHZ	2.0m	20.0	17.8
SC3316FH-R56	0.56	100KHZ	5.0m	13.0	11.5
SC3316FH-1R0	1.0	100KHZ	6.0m	11.0	10.5
SC3316FH-1R5	1.5	100KHZ	8.0m	9.0	8.5
SC3316FH-2R2	2.2	100KHZ	11.0m	7.8	7.4
SC3316FH-2R7	2.7	100KHZ	12.0m	7.0	6.4
SC3316FH-3R3	3.3	100KHZ	14.0m	6.4	6.4
SC3316FH-4R7	4.7	100KHZ	18.0m	5.4	5.4
SC3316FH-6R8	6.8	100KHZ	22.0m	5.0	4.5





(1). Inductance tolerance for 0.27uH~3.3uH: ±30%, for 4.7uH~6.8uH: ±20%. Tested at 0.25V, 0ADC and 25℃.
(2). DCR measured at 25℃.
(3). The DC current at which the inductance decreases by 10% from its initial value.
(4). The DC current that results in a 40℃ temperature rise from 25℃ ambient.

Click here for QUANTITY PER REEL & PACKING INFORMATION

Custom versions available upon request.

©2011 Signal Transformer –Specification subject to change without notice. 07.11

Signal Transformer
www.signaltransformer.com
500 Bayview Avenue, Inwood, NY 11096
Toll Free 866-239-5777 • Tel 516-239-5777 • Fax 516-239-7208
Sales@signaltransformer.com • techhelp@signaltransformer.com

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Bel:
SC3316FH-R56 SC3316FH-1R5 SC3316FH-6R8 SC3316FH-1R0 SC3316FH-2R2 SC3316FH-3R3 SC3316FH-2R7 SC3316FH-4R7 SC3316FH-R27