


REV. 0
DCO 142387

| | |
|-----------------|----------------------------|
| COIL: @ 25°C | |
| RESISTANCE | 50 OHMS ±10% |
| NOMINAL VOLTAGE | 5.0 VDC |
| MUST OPERATE | 2.7 VDC |
| MUST RELEASE | 1.4 VDC MAX, 0.22 VDC MIN. |

| | |
|--------------|-----------------------------|
| ENVIRONMENT: | |
| VIBRATION | 10 CPS TO 3000 CPS @ 30 g's |
| SHOCK | 75 g's 6 MS. DURATION |
| TEMPERATURE | -65 °C TO +125 °C |

| | |
|--------|---------------------------------------|
| NOTES: | OPERATE TIME 2.0 MS MAX |
| | RELEASE TIME 4.0 MS MAX |
| | CONTACT STABILIZATION TIME 2.5 MS MAX |

CUSTOMER DATA SHEET



CONTACT RATING: LOW LEVEL TO 1 AMP
28 VDC RESISTIVE 100,000 OPERATIONS

DR. PBB 10/12/00 CK. TCG 10-12-00

IIII Technologies
advanced control electronic solutions

CUST. QPL
CUST. NO. M39016/18-049P REV.

JMGAD RELAY

JMGACDG-5PW

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[JMGACDG-5PW](#)