





LOC	DIST	REVISIONS				
		P	LTR	DESCRIPTION	DATE	APVD
-	-	-	-	SEE SHEET 1	-	-


4-1971904-2 AS SHOWN



NOTE:
1. APPLICABLE P/N PLUG HOUSING: *-1971905-*
APPLICABLE P/N CONTACT: 1971795-1.
2. APPLICABLE WIRE RANGE: AWG28~AWG26
INSULATION DIA: Ø0.8-Ø1.2MM
3. MATERIAL:
THERMAL PLASTIC MATERIAL, (UL94 V-0)

P/N	Pos.	DIM.A	DIM.B	COLOR
4-1971904-2	4	9.5	7.5	YELLOW
4-1971904-3	6	12.8	10.8	



THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN ANNIE QIAN 01APR2015	 TE Connectivity				
DIMENSIONS: mm		CHK ANNIE QIAN 01APR2015	NAME NEXT GENERATION GI3.3				
		APVD DANIEL ZHANG 01APR2015					
TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ± 1 PLC ± 2 PLC ±0.20 3 PLC ± 4 PLC ± ANGLES ±1		PRODUCT SPEC 108-106094	- -				
		APPLICATION SPEC 114-106094					
		WEIGHT -	SIZE A3	CAGE CODE -	DRAWING NO C-1971904	RESTRICTED TO -	
		CUSTOMER DRAWING		SCALE N/A	SHEET 2 OF 3		
MATERIAL -		FINISH -					

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[2-1971904-4](#)