XB5KSB

annunciator 24 V AC/DC 85 dB

Product availability: Stock - Normally stocked in distribution facility



Main

Commercial Status	Commercialised
Range of product	Harmony XB5
Bezel material	Plastic
Product or component type	Annunciator
Mounting diameter	0.87 in (22 mm)

Complementary

[Us] rated supply voltage	24 V (+/- 10 %)	
Supply circuit type	AC/DC	
Supply frequency	50/60 Hz	
Current consumption	5 mA	
Signalling type	Continuous or intermittent tone	
Resistance to high pressure washer	1015.26 psi (7000000 Pa) at 131 °F (55 °C),distance: 0.1 m	
Height	1.18 in (30 mm)	
Width	1.18 in (30 mm)	
Depth	2.36 in (60 mm)	
Product weight	0.08 lb(US) (0.035 kg)	

Environment

Liviloiment	
Noise level	85 dB
Vibration frequency	4 kHz
Protective treatment	TH
Ambient air temperature for storage	-40158 °F (-4070 °C)
Ambient air temperature for operation	-13158 °F (-2570 °C)
Class of protection against electric shock	Class II conforming to IEC 60536
IP degree of protection	IP40 conforming to IEC 60529
NEMA degree of protection	NEMA 1
IK degree of protection	IK03 conforming to IEC 50102 IK03 conforming to EN 50102
Standards	EN 60947-1 EN 60947-5-1 EN 60947-5-4 IEC 60947-1 IEC 60947-5-1 IEC 60947-5-1 IEC 60947-5-4 JIS C 4520 UL 508 CSA C22.2 No 14
Product certifications	BV CSA DNV GL LROS (Lloyds register of shipping) RINA UL listed

Ordering and shipping details

Category	22467 - PUSHBUTTONS,22MM(PLASTIC) NEW	
Discount Schedule	CS2	
GTIN	00785901396192	
Nbr. of units in pkg.	1	
Package weight(Lbs)	0.06	
Product availability	Stock - Normally stocked in distribution facility	
Returnability	Υ	
Country of origin	FR	

Contractual warranty

Period	18 months



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Schneider Electric: XB5KSB