



Bestückungsplan / contact layout

■ bestückt / assemble



Leiterplatten-Lochbild / PCB drillhole pattern



Tauchlötanschluß 0,65 x 0,3 mm / solder terminal 0,65 x 0,3 mm

Isolierwerkstoff / housing material : PBT GF30

Bauart 7 / type 7


Anforderungsstufe 2 = 400 Steckzyklen / performance class 2 = 400 mating cycles

Fehlende Maße und Angaben nach IEC 60 603-2 / DIN EN 60 603-2

Missing information and dimensions per IEC 60 603-2

Bedruckung siehe Zeichnung 294875

Marking see drawing 294875

Consider protection memo from DIN 34	Information: Halteöse auf Pos. a1, a2, e31, e32 retaining loop at pos. a1, a2, e31, e32		Tolerances  All Dimensions in mm		Scale 2:1	
	All rights reserved. Only for information. To insure that this is the latest version of this drawing, please contact one of the ERNI companies before using.		Subject to modification without prior notice. Drawing will not be updated.		Designation Federleiste E 160 Löt <i>Fem. Connector E 160 Solder</i>	
	ERNI		www.ERNI.com		284313	
b	21.09.2009			I		
Index	Date	H:00068425.SZA		STVE		

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[ERNI Electronics:](#)

[284313](#)