



INK STAMP PART NO. & DATE CODE  
.047 [1.19] MIN. HIGH

- MATERIAL & FINISH  
SHELL: DIE CAST ALUM. ALLOY PER FED SPEC QQ-A-591  
FINISH: CAD. PLATED PER QQ-P-416, TYPE I, CLASS 2  
YELLOW CHROMATE CONVERSION.  
INSULATOR, HARD: EPOXY PER MIL-M-24325.  
INSULATOR, SOFT: FLUOROSILICONE RUBBER, COLOR: BLUE.  
GROMMET PROTECTOR: ALUM. ALLOY, FINISH: BLUE EPOXY.  
POLARIZING POST & NUTS: STAINLESS STEEL.  
MALE JACKSCREW: STAINLESS STEEL.  
SCREWS & WASHERS: STEEL, CAD. PLATED PER QQ-P-416.  
DUST CAP: CLEAR VINYL.

CONTACTS SHOWN IN POSITION FOR ILLUSTRATION ONLY, ARE INCLUDED IN A CONTAINER WITHIN CONNECTOR PACKAGE FOR SHIPMENT, EXCEPT P/N'S 1-207596-1 THRU 2-207596-0.

- COAX CONTACTS & SEALING BOOTS MUST BE ORDERED SEPARATELY.
- FOR CONTACT SIZE 22 DIMENSION "B" REPRESENTS PIN CONTACTS & DIMENSION "D" REPRESENTS SOCKET CONTACTS.
- ALL METRIC DIMENSIONS ARE SHOWN IN PARENTHESIS.
- FOR MATING CONNECTOR SEE 207595.
- CONNECTORS ORDERED LESS CONTACTS WILL BE MARKED WITH SAME P/N AS CONNECTORS ORDERED WITH CONTACTS.

"B"				"C"				"D"			
22	20	16	12	22	20	16	12	22	20	16	12
.736	.827	.782	.793	.797	.893	.893	.893	.737	.700	.824	.824
[18.69]	[21.00]	[19.86]	[20.14]	[20.24]	[22.68]	[22.68]	[22.68]	[18.72]	[17.78]	[20.93]	[20.93]
.688	.769	.735	.746	.769	.865	.865	.865	.688	.585	.746	.746
[17.48]	[19.53]	[18.67]	[18.95]	[19.53]	[21.97]	[21.97]	[21.97]	[17.48]	[14.86]	[18.95]	[18.95]

"A"	INSERT ARRANGEMENT			
	26	32C2	67	106
1.541	1.625	1.425	1.541	
[39.14]	[41.28]	[36.20]	[39.14]	

PART NO.	ARRANGEMENT		PART NO. (LESS CONTACTS)
	IN MODULE "A"	IN MODULE "B"	
207596-1	(106S)	(67P)	1-207596-1
OBSOLETE 207596-2	(106S)	(26P)	1-207596-2
207596-3	(106S)	(106S)	1-207596-3
OBSOLETE 207596-4	(106S)	(106P)	1-207596-4
207596-5	(106P)	(106P)	1-207596-5
OBSOLETE 207596-6	(106P)	(26S)	1-207596-6
207596-7	(106P)	(67S)	1-207596-7
OBSOLETE 207596-8	(106P)	(67P)	1-207596-8
207596-9	(106P)	(32C2S)	1-207596-9
1-207596-0	(106S)	(32C2P)	2-207596-0

  

THIS DRAWING IS A CONTROLLED DOCUMENT.		DIN J. KAISER 23-SEP-03	
DIMENSIONS: INCHES		CIK J. MARKEY 23-SEP-03	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD J. MARKEY 23-SEP-03	
0 PLC	± .005(0.13)	NAME	
1 PLC	± .005(0.13)	PLUG CONNECTOR	
2 PLC	± .005(0.13)	INSTALLATION	
3 PLC	± .005(0.13)	(WITH CENTER MALE JACKSCREW)	
4 PLC	± .005(0.13)	SIZE	
ANGLES	± .005(0.13)	CODE	
MATERIAL		DRAWING NO	
FINISH		A1 00779 C=207596	
CUSTOMER DRAWING		RESTRICTED TO	
SCALE 3:1		SHEET 1 OF 1	
REV R			

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[2-207596-0](#)