



LOADING PATTERN MATING SIDE

f	6	6	6	6	6	6	6	6	6	6	6
e	4	4	4	4	4	4	4	4	4	4	4
d	4	4	4	4	4	4	4	4	4	4	4
c	4	4	4	4	4	4	4	4	4	4	4
b	4	4	4	4	4	4	4	4	4	4	4
a	4	4	4	4	4	4	4	4	4	4	4
z	6	6	6	6	6	6	6	6	6	6	6
P	0		0		5		1		0		
O	1										
S											

LOADED CONNECTOR ASSEMBLY  
(FOR EXAMPLE)




CONTACT OVERVIEW



PLATING TABLE

CODE	PLATING	CONTACT AREA	TYPE OF TERMINAL	PERFORMANCE LEVEL
AA	0.75 $\mu$ Au	GOLD OVER NICKEL PLATING.	SHORT TERMINAL EON PRESSFIT CONTACTS	IEC PERFORMANCE LEVEL 2 (250 mating cycles) or TELCORDIA CO
AB	1.25 $\mu$ Au	GOLD OVER NICKEL PLATING.	SHORT TERMINAL EON PRESSFIT CONTACTS	TELCORDIA UE

LAY-OUT P.C.B.-HOLE



NOTES

1. THIS PRODUCT IS CSA APPROVED.
2. THIS PRODUCT IS UL RECOGNIZED.
3. MEASURED AT THE BOTTOM.
4. MATERIAL CONTACT: PHOSPHOR BRONZE
5. HOUSING : CREAM WHITE GLASS FILLED POLYESTER UL-94V0
6. CONNECTOR PRINTED WITH P/N AND DATE CODE.
7. FOR ACTUAL CONTACT LOADINGS, SEE LOADING PATTERN MATING SIDE.
8. SHAPE OF CONNECTOR HOUSING CAN ALTER DEPENDING ON PRODUCTION LOCATION
9. THE PRODUCT (LF) MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008
10. FOR RECOMMENDED PTH DIMENSIONS REFER DRAWING : BS, A , 201572 , 001

CATALOG NO: HM2P09PA5111----

mat'l. code SEE NOTE 4				surface ISO 1302	tolerance ISO 406 ISO 1101	projection	product family MILLIPACS
ltr	ecn no	dr	date	tolerances unless otherwise specified			
A	I09-0210	MINI	2009-10-06	angles		.0±0.2	
B	I09-0290	AB	2009-12-29	linear		.00±0.1	
C	I10-0018	MINI	2010-01-13	0°±1°			
				dr	MINI K VANDANATH	2009-10-06	
				engr	ALEX BABU	2009-10-06	
				chr	ALEX BABU	2009-10-06	
				appd	ALEX BABU	2009-10-06	
sheet index		revision sheet	c				
		1					



dwg no sheet 1 of 1 size  
BS, C , 203032, 009 A.3  
type Product Customer Drawing

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[FCI / Amphenol:](#)

[HM2P09PA5111AALF](#)