

4 USE WITH 22-26 AWG WIRE SIZE, .050 MAX INSULATION DIA., .015 MAX INSULATION WALL THICKNESS.

CONTACT IDENTIFICATION NUMBER "2" LOCATED IN THIS AREA. 5

.000050 MIN W.E. #1 GOLD ALLOY IN CONTACT AREA, .000050 - .000100 TIN IN AREA D, ALL OVER .000050 NICKEL. 6ROHS 2002/95/EC COMPLIANT /7

OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI 8

D

С

В

А

2					1			
LOC)C	DIST			REVISIONS			
A	AD	00	Р	LTR	DESCRIPTION	DATE	DWN	APVD
				L	EC 0G3C 0675 04	08JAN04	BSV	DFR
				L1	REVISED PER ECO-09-020932	27AUG09	KK	AEG

R.091±.005 TYP

.125

		.400	.300	3	8	5-104305-4		
/8/OBSOL	ETE $7\sqrt{6}$	1.000	.900	9	20	5-104305-3		
	7/6	1.700	1.600	16	34	5-104305-2		
		.500	.400	4	10	5-104305-1		
		.400	.300	3	8	104305-4		
		1.000	.900	9	20	104305-3		
		1.700	1.600	16	34	104305-2		
		.500	.400	4	10	104305-1		
		С	В	A	NO OF POSN	ASSEMBLY PART NUMBER		
THIS DRAWING IS A CONTROLLED DOCUMENT. DWN 11-20-87 H MOLL CHK 11-20-87			Tyco Electronics Corporation Electronics Harrisburg, Pa 17105–3608					
DIMENSIONS: INCHES O PLC ± - 1 PLC ± - 2 PLC ± - 3 PLC ± .005 4 PLC ± - ANGLES ± - ANGLES ± - ANGLES ± -	PRODUCT Spec 108-2501 APPLICATION MEIGHT	517	NAME RECEPTACLE ASSY, AMPMODU, MASS TERMINATION, DBL ROW, .100 X .100 CL, #22-#26 AWG WIRE SIZE CAGE CODE DRAWING NO A 2 00779 C-104305					
THERMOPLASTIC, COLOR:BLACK CONTACTS: PHOS BRONZE	CUSTOMER DRA	WING)		HEET OF REV		

D

С

104305

В

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

TE Connectivity: 104305-2