





2.5×2.0mm for Consumer Products/ Mobile Communications



RoHS Compliant

Features

- Crystal unit for Consumer Products
- Ceramic package
- · Reflow compatible

Applications

- Digital Electronics
- Consumer Products
- Mobile Communications, Bluetooth®, Wireless LAN
- * Bluetooth® Trademarks are owned by Bluetooth SIG, Inc.

How to Order

CX2520DB	27000	D0	G		J	CC
1	2	3	4	(5)	6	7

OSeries

©Frequency

3Load Capacitance @Frequency Tolerance

Loud Capacitaries		Orrequency folerance				
00	8 pF	G	±15×10 ⁻⁶			

⑤Operating Temp. Range ⑥Frequency Temp. Stability

EJ	−10 to +70°C	$\pm 15 \times 10^{-6}$		
LN	−30 to +85°C	±25×10 ⁻⁶		

OIndividual Specification (STD Specification is "CC".)

Packaging (Tape & Reel 1000/ 3000/ 12000 pcs./ reel)

Specifications

Item	Symbol	Specification	Unit	Remarks
Frequency Range	f_nom	12000 to 54000	kHz	
Overtone Order	ОТ	Fundamental		
Load Capacitance	CL	8	pF	Please contact us for other CL requirements.
Frequency Tolerance	f_tol	±15	×10 ⁻⁶	25°C±3°C
Motional Series Resistance	R1	Table 1	ohm	
Drive Level	DL	Table 2	μW	
Operating Temp. Range	T_use	-10 to +70 -30 to +85	°C	
Storage Temp. Range	T_stg	-40 to +85	°C	
Frequency Temp. Characteristics	f_tem	±15	×10 ⁻⁶	Freq. deviation from the value at 25°C


Please contact us for other specifications.

Table 1 Motional Series Resistance

Frequency Range	Motional Series Resistance
12000≤f_nom<16000kH	150 Ω max.
16000≤f_nom<26000kH	80 Ω max.
26000≤f_nom<30000kH	60 Ω max.
30000≤f_nom≤54000kH	Iz 50 Ω max.


Table 2 Level of Drive

Frequency Range	Level of Drive
12000≤f_nom≤54000kHz	10μW (100μW max.)



Recommended Land Pattern





Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Kyocera:

```
CX2520DB16000D0FLJZ1
CX2520DB16000D0GEJZ1
CX2520DB20000D0FLJZ1
CX2520DB24000D0GEJZ1

CX2520DB24576D0GEJZ1
CX2520DB27000B0FLHA1
CX2520DB27000H0KLSA1
CX2520DB30000D0GEJZ1

CX2520DB32000D0FLJZ1
CX2520DB32000D0GEJZ1
CX2520DB40000D0FLJZ1
CX2520DB48000D0FLJZ1
CX2520DB48000D0GEJCC

CX2520DB26000D0FLJZ1
CX2520DB384000D0FLJZ2
CX2520DB384000D0FLJCC
CX2520DB382000D0FLJCC
CX2520DB382000D0FLJCC

CX2520DB20000D0FLJCC
CX2520DB32000D0GEJCC
CX2520DB32000D0FLJCC
CX2520DB32000D0GEJCC

CX2520DB24000D0GEJCC
CX2520DB32000D0GEJCC
CX2520DB38400D0FLJCC
CX2520DB38400D0FLJCC

CX2520DB16000D0WZRC1
CX2520DB32000D0WZRC1
CX2520DB16000E0FGHCC
CX2520DB32000F0FPLCC

CX2520DB16000D0FDFC1
CX2520DB16000D0FFHCC
CX2520DB26000E0FGGCC
CX2520DB26000E0FGGCC
```