


## Interference Suppression Film Capacitor - Class X2 Radial MKT - 310 V<sub>AC</sub> - Series Impedance - 85 °C / 85 % RH


**FEATURES**

- Stable capacitance in severe ambient conditions 85 °C; 85 % RH, 240 V<sub>AC</sub>, 1000 h
- 15 mm to 27.5 mm lead pitch
- Material categorization:  
for definitions of compliance please see [www.vishay.com/doc?99912](http://www.vishay.com/doc?99912)




**RoHS**  
COMPLIANT  
HALOGEN  
**FREE**  
**GREEN**  
(5-2008)

**APPLICATIONS**


High stability grade X2 capacitors for series impedance and across the line applications.

See also application note: [www.vishay.com/doc?28153](http://www.vishay.com/doc?28153)

QUICK REFERENCE DATA	
Capacitance range (E12 series)	10 nF to 2.2 µF (preferred values according to E6)
Capacitance tolerance	± 10 %; ± 20 %
Rated AC voltage	310 V <sub>AC</sub>
Climatic testing class according to IEC 60068-1	55/110/56
Rated temperature	C ≤ 1 µF: 110 °C C > 1 µF: 105 °C
Reference standards	IEC 60384-14 ed-4 and EN 60384-14 IEC 60065 requires pass. flamm. class: B for volumes > 1750 mm <sup>3</sup> C for volumes ≤ 1750 mm <sup>3</sup> UL 60384-14; CSA-E384-14
Dielectric	Polyester film
Electrodes	Metallized
Construction	Series construction 
Encapsulation	Plastic case, epoxy resin sealed, flame retardant UL-class 94 V-0
Leads	Tinned wire
Marking	C-value; tolerance; rated voltage; sub-class; manufacturer's type; code for dielectric material; manufacturer location, year and week; manufacturer's logo or name; safety approvals


**Notes**

- For more detailed data and test requirements, contact [rfi@vishay.com](mailto:rfi@vishay.com)
- For general information like characteristics and definitions used for film capacitors follow the link: [www.vishay.com/doc?28147](http://www.vishay.com/doc?28147)

DIMENSIONS in millimeters




**COMPOSITION OF CATALOG NUMBER**



**Notes**

- For detailed tape specifications refer to packaging information [www.vishay.com/doc?28139](http://www.vishay.com/doc?28139)
- <sup>(1)</sup> Packaging will be bulk for all capacitors with pitch  $\leq$  15 mm and such with long leads ( $>$  5 mm). Capacitors with short leads up to 5 mm and pitch  $>$  15 mm will be in tray and asking code will be "T".



SPECIFIC REFERENCE DATA	
DESCRIPTION	VALUE
Rated AC voltage ( $U_{RAC}$ )	310 V <sub>AC</sub>
Rated DC voltage ( $U_{RDC}$ )	630 V <sub>DC</sub>
Tangent of loss angle	$\leq 100 \times 10^{-4}$ at 1 kHz
Rated voltage pulse slope ( $dU/dt$ ) <sub>R</sub> at 435 V <sub>DC</sub>	100 V/ $\mu$ s
R between leads, for $C \leq 0.33 \mu$ F at 100 V; 1 min	$> 15\,000 \text{ M}\Omega$
RC between leads, for $C > 0.33 \mu$ F at 100 V; 1 min	$> 5000 \text{ s}$
R between leads and case; 100 V; 1 min	$> 30\,000 \text{ M}\Omega$
Withstanding (DC) voltage (cut off current 10 mA) <sup>(1)</sup> ; rise time $\leq 1000 \text{ V/s}$ : C $\leq 1.0 \mu$ F C $> 1.0 \mu$ F	1800 V; 1 min 1500 V; 1 min
Withstanding (AC) voltage between leads and case	2120 V; 1 min
Maximum application temperature	C $\leq 1 \mu$ F: 110 °C C $> 1 \mu$ F: 105 °C

Note

<sup>(1)</sup> See "Voltage Proof Test for Metalized Film Capacitors": [www.vishay.com/doc?28169](http://www.vishay.com/doc?28169)

ELECTRICAL DATA AND ORDERING INFORMATION											
$U_{RAC}$ (V)	CAP. ( $\mu$ F)	DIMENSIONS w x h x l (mm)	MASS (g) <sup>(3)</sup>	CATALOG NUMBER F1772S X2... AND PACKAGING							
				LOOSE IN BOX					REEL <sup>(1)(2)</sup>		
				SHORT LEADS			LONG LEADS		$\varnothing = 500 \text{ mm}$ $H = 18.5 \text{ mm};$ $P_0 = 12.7 \text{ mm}$	SPQ	
				$l_t = 3.5 \text{ mm}$ $\pm 0.3 \text{ mm}$	$l_t = 5.0 \text{ mm}$ $\pm 1.0 \text{ mm}$	SPQ	$l_t = 25.0 \text{ mm}$ $\pm 2.0 \text{ mm}$	SPQ			
<b>PITCH = 15 mm <math>\pm</math> 0.4 mm; <math>d_t = 0.60 \text{ mm} \pm 0.06 \text{ mm}</math>; C-TOL. = <math>\pm 20 \%</math></b>											
310	0.010	5.0 x 11.0 x 17.5	1.0	31031MFPB0	31031MFMB0	1250	31031MFIB0	1000	31031MFOW0	1100	
	0.015			31531MFPB0	31531MFMB0		31531MFIB0		31531MFOW0		
	0.022			32231MFPB0	32231MFMB0		32231MFIB0		32231MFOW0		
	0.033			33331MFPB0	33331MFMB0		33331MFIB0		33331MFOW0		
	0.047			34731MFPB0	34731MFMB0		34731MFIB0		34731MFOW0		
	0.068	6.0 x 12.0 x 17.5	1.4	36831MFPB0	36831MFMB0	1000	36831MFIB0	1000	36831MFOW0	900	
	0.10			41031MFPB0	41031MFMB0		41031MFIB0		41031MFOW0		
	<b>PITCH = 15 mm <math>\pm</math> 0.4 mm; <math>d_t = 0.80 \text{ mm} \pm 0.08 \text{ mm}</math>; C-TOL. = <math>\pm 20 \%</math></b>										
		0.15	8.5 x 15.0 x 17.5	2.4	41531MFPB0	41531MFMB0	750	41531MFIB0	500	41531MFOW0	650
		0.22	10.0 x 16.5 x 17.5	3.0	42231MFPB0	42231MFMB0	500	42231MFIB0	450	42231MFOW0	600
	0.33	10.5 x 17.5 x 18.0	4.0	43331MFPB0	43331MFMB0	250	43331MFIB0	400	43331MFOW0	600	
<b>PITCH = 15 mm <math>\pm</math> 0.4 mm; <math>d_t = 0.60 \text{ mm} \pm 0.06 \text{ mm}</math>; C-TOL. = <math>\pm 10 \%</math></b>											
310	0.010	5.0 x 11.0 x 17.5	1.0	31031KFPB0	31031KFMB0	1250	31031KFIB0	1000	31031KFOW0	1100	
	0.012			31231KFPB0	31231KFMB0		31231KFIB0		31231KFOW0		
	0.015			31531KFPB0	31531KFMB0		31531KFIB0		31531KFOW0		
	0.018			31831KFPB0	31831KFMB0		31831KFIB0		31831KFOW0		
	0.022			32231KFPB0	32231KFMB0		32231KFIB0		32231KFOW0		
	0.027			32731KFPB0	32731KFMB0		32731KFIB0		32731KFOW0		
	0.033			33331KFPB0	33331KFMB0		33331KFIB0		33331KFOW0		
	0.039			33931KFPB0	33931KFMB0		33931KFIB0		33931KFOW0		
	0.047			34731KFPB0	34731KFMB0		34731KFIB0		34731KFOW0		
	0.056			35631KFPB0	35631KFMB0		35631KFIB0		35631KFOW0		
	0.068	6.0 x 12.0 x 17.5	1.4	36831KFPB0	36831KFMB0	1000	36831KFIB0	1000	36831KFOW0	900	
	0.082			38231KFPB0	38231KFMB0		38231KFIB0		38231KFOW0		
	<b>PITCH = 15 mm <math>\pm</math> 0.4 mm; <math>d_t = 0.80 \text{ mm} \pm 0.08 \text{ mm}</math>; C-TOL. = <math>\pm 10 \%</math></b>										
		0.10	7.0 x 13.5 x 17.5	1.8	41031KFPB0	41031KFMB0	750	41031KFIB0	500	41031KFOW0	800
	0.12	41231KFPB0			41231KFMB0	41231KFIB0		41231KFOW0			
	0.15	8.5 x 15.0 x 17.5	2.4	41531KFPB0	41531KFMB0	750	41531KFIB0	500	41531KFOW0	650	
	0.18			41831KFPB0	41831KFMB0		41831KFIB0		41831KFOW0		
	0.22	10.0 x 16.5 x 17.5	3.0	42231KFPB0	42231KFMB0	500	42231KFIB0	450	42231KFOW0	600	
	0.27	10.5 x 17.5 x 18.0	4.0	42731KFPB0	42731KFMB0	250	42731KFIB0	400	42731KFOW0	600	
	0.33	11.0 x 18.5 x 18.0	5.0	43331KFPB0	43331KFMB0	225	43331KFIB0	350	43331KFOW0	550	



ELECTRICAL DATA AND ORDERING INFORMATION										
U <sub>RAC</sub> (V)	CAP. (μF)	DIMENSIONS w x h x l (mm)	MASS (g) <sup>(3)</sup>	CATALOG NUMBER F1772S X2... AND PACKAGING						
				LOOSE IN BOX					REEL <sup>(1)(2)</sup>	
				SHORT LEADS			LONG LEADS		Ø = 500 mm H = 18.5 mm; P <sub>0</sub> = 12.7 mm	SPQ
				l <sub>t</sub> = 3.5 mm ± 0.3 mm	l <sub>t</sub> = 5.0 mm ± 1.0 mm	SPQ	l <sub>t</sub> = 25.0 mm ± 2.0 mm	SPQ		
PITCH = 22.5 mm ± 0.4 mm; d <sub>t</sub> = 0.80 mm ± 0.08 mm; C-TOL. = ± 20 %										
0.15	6.0 x 15.5 x 26.0	2.4	41531MIPT0	41531MIMT0	300	41531MIIB0	250	41531MIOW0	600	
0.22	7.0 x 16.5 x 26.0	2.9	42231MIPT0	42231MIMT0	200	42231MIIB0	250	42231MIOW0	500	
0.33	8.5 x 18.0 x 26.0	3.8	43331MIPT0	43331MIMT0	200	43331MIIB0	250	43331MIOW0	450	
0.41			44131MIPT0	44131MIMT0		44131MIIB0		44131MIOW0		
0.47	10.0 x 19.5 x 26.0	6.8	44731MIPT0	44731MIMT0	200	44731MIIB0	200	44731MIOW0	350	
0.68	12.0 x 22.0 x 26.0	7.8	46831MIPT0	46831MIMT0	150	46831MIIB0	200	46831MIOW0	300	
1.0	15.5 x 26.5 x 26.5	9.0	51031MIPT0	51031MIMT0	110	51031MIIB0	275	51031MIOW0	250	
1.5	18.0 x 29.5 x 26.5	10.0	51531MIPT0	51531MIMT0	90	51531MIIB0	250	51531MIOW0	200	
PITCH = 22.5 mm ± 0.4 mm; d <sub>t</sub> = 0.80 mm ± 0.08 mm; C-TOL. = ± 10 %										
0.10	6.0 x 15.5 x 26.0	2.4	41031KIPT0	41031KIMT0	300	41031KIIB0	250	41031KIOW0	600	
0.12			41231KIPT0	41231KIMT0		41231KIIB0		41231KIOW0		
0.15	7.0 x 16.5 x 26.0	2.9	41531KIPT0	41531KIMT0	200	41531KIIB0	250	41531KIOW0	500	
0.18			41831KIPT0	41831KIMT0		41831KIIB0		41831KIOW0		
0.22	8.5 x 18.0 x 26.0	3.8	42231KIPT0	42231KIMT0	200	42231KIIB0	250	42231KIOW0	450	
0.27			42731KIPT0	42731KIMT0		42731KIIB0		42731KIOW0		
0.33	10.0 x 19.5 x 26.0	6.8	43331KIPT0	43331KIMT0	200	43331KIIB0	200	43331KIOW0	350	
0.39			43931KIPT0	43931KIMT0		43931KIIB0		43931KIOW0		
0.41	12.0 x 22.0 x 26.0	7.8	44131KIPT0	44131KIMT0	150	44131KIIB0	200	44131KIOW0	300	
0.47			44731KIPT0	44731KIMT0		44731KIIB0		44731KIOW0		
0.56	12.5 x 22.5 x 26.5	8.2	45631KIPT0	45631KIMT0	140	45631KIIB0	400	45631KIOW0	300	
0.68			46831KIPT0	46831KIMT0		46831KIIB0		46831KIOW0		
0.82	15.5 x 26.5 x 26.5	9.0	48231KIPT0	48231KIMT0	110	48231KIIB0	275	48231KIOW0	250	
1.0			51031KIPT0	51031KIMT0		51031KIIB0		51031KIOW0		
1.2	51231KIPT0	51231KIMT0	51231KIIB0	51231KIOW0						
PITCH = 27.5 mm ± 0.4 mm; d <sub>t</sub> = 0.80 mm ± 0.08 mm; C-TOL. = ± 20 %										
0.39	9.0 x 19.0 x 31.5	5.5	43931MKPT0	43931MKMT0	100	43931MKIB0	150	-	-	
0.41			44131MKPT0	44131MKMT0		44131MKIB0				
0.47	11.0 x 21.0 x 31.0	7.4	44731MKPT0	44731MKMT0	100	44731MKIB0	125	-	-	
0.68			46831MKPT0	46831MKMT0		46831MKIB0				
1.0	15.0 x 23.0 x 31.0	11.0	51031MKPT0	51031MKMT0	100	51031MKIB0	100	-	-	
1.5	18.0 x 28.0 x 31.5	12.3	51531MKPT0	51531MKMT0	100	51531MKIB0	100	-	-	
2.2	21.0 x 31.0 x 31.0	16.1	52231MKPT0	52231MKMT0	50	52231MKIB0	75	-	-	
PITCH = 27.5 mm ± 0.4 mm; d <sub>t</sub> = 0.80 mm ± 0.08 mm; C-TOL. = ± 10 %										
0.39	9.0 x 19.0 x 31.5	5.5	43931KKPT0	43931KKMT0	100	43931KKIB0	150	-	-	
0.41			44131KKPT0	44131KKMT0		44131KKIB0				
0.47	11.0 x 21.0 x 31.0	7.4	44731KKPT0	44731KKMT0	100	44731KKIB0	125	-	-	
0.56			45631KKPT0	45631KKMT0		45631KKIB0				
0.68	15.0 x 25.0 x 31.5	11.0	46831KKPT0	46831KKMT0	100	46831KKIB0	125	-	-	
0.82			48231KKPT0	48231KKMT0		48231KKIB0				
1.0	18.0 x 28.0 x 31.5	12.3	51031KKPT0	51031KKMT0	100	51031KKIB0	100	-	-	
1.2			51231KKPT0	51231KKMT0		51231KKIB0				
1.5	21.0 x 31.0 x 31.0	16.1	51531KKPT0	51531KKMT0	50	51531KKIB0	75	-	-	
1.8			51831KKPT0	51831KKMT0		51831KKIB0				
2.2	52231KKPT0	52231KKMT0	52231KKIB0	52231KKIB0						

Notes

- SPQ = Standard Packing Quantity
- (1) Reel diameter = 356 mm is available on request
- (2) H = in-tape height; P<sub>0</sub> = sprocket hole distance; for detailed specifications refer to "Packaging Information"
- (3) Weight for short lead product only

APPROVALS				
SAFETY APPROVALS X2	VOLTAGE	VALUE	FILE NUMBERS	LINK
EN 60384-14 (ENEC) (= IEC 60384-14 ed-4)	310 V <sub>AC</sub>	0.01 µF to 2.2 µF X2	40005079	<a href="http://www.vishay.com/doc?28225">www.vishay.com/doc?28225</a>
UL 60384-14	310 V <sub>AC</sub>	0.01 µF to 2.2 µF X2	E354331	<a href="http://www.vishay.com/doc?28231">www.vishay.com/doc?28231</a>
CSA-E384-14	310 V <sub>AC</sub>	0.01 µF to 2.2 µF X2	E354331	
CB-test certificate	310 V <sub>AC</sub>	0.01 µF to 2.2 µF X2	DE1-58410	<a href="http://www.vishay.com/doc?28226">www.vishay.com/doc?28226</a>
The ENEC-approval together with the CB-certificate replace all national marks of the following countries (they have already signed the ENEC-agreement): Austria; Belgium; Czech Republic; Denmark; Finland; France; Germany; Greece; Hungary; Ireland; Italy; Luxembourg; Netherlands; Norway; Portugal; Slovenian; Spain; Sweden, Switzerland and United Kingdom.				

## MOUNTING

### Normal Use

The capacitor unit is designed for mounting on a printed-circuit board. The capacitors packed in bandoliers are designed for mounting on printed-circuit boards by means of automatic insertion machines.

For detailed tape specifications refer to packaging information [www.vishay.com/docs?28139](http://www.vishay.com/docs?28139)

### Specific Method of Mounting to Withstand Vibration and Shock

In order to withstand vibration and shock tests, it must be ensured that the stand-off pips are in good contact with the printed-circuit board. The capacitor shall be mechanically fixed by the leads and the body clamped.


- For pitches  $\leq 15$  mm the capacitors shall be mechanically fixed by the leads
- For larger pitches the capacitors shall be mounted in the same way and the body clamped

### Space Requirements on Printed-Circuit Board

The maximum space for length ( $l_{max.}$ ), width ( $w_{max.}$ ) and height ( $h_{max.}$ ) of film capacitors to take in account on the printed circuit board is shown in the drawings.

- For products with pitch  $\leq 15$  mm,  $\Delta w = \Delta l = 0.3$  mm and  $\Delta h = 0.1$  mm
- For products with  $15$  mm  $<$  pitch  $\leq 27.5$  mm,  $\Delta w = \Delta l = 0.5$  mm and  $\Delta h = 0.1$  mm

Eccentricity defined as in drawing. The maximum eccentricity is smaller than or equal to the lead diameter of the product concerned.





**SOLDERING CONDITIONS**

For general soldering conditions and wave soldering profile we refer to the document "Soldering Guidelines for Film Capacitors": [www.vishay.com/doc?28171](http://www.vishay.com/doc?28171)

**Storage Temperature**


T<sub>stg</sub> = -25 °C to +35 °C with RH maximum 75 % without condensation

**Ratings and Characteristics Reference Conditions**


Unless otherwise specified, all electrical values apply to an ambient temperature of 23 °C ± 1 °C, an atmospheric pressure of 86 kPa to 106 kPa and a relative humidity of 50 % ± 2 %.

For reference testing, a conditioning period shall be applied over 96 h ± 4 h by heating the products in a circulating air oven at the rated temperature and a relative humidity not exceeding 20 %.


**CHARACTERISTICS**




Capacitance as a function of ambient temperature (typical curve)




Impedance as a function of frequency (typical curve)



Tangent of loss angle as a function of frequency (typical curve)



Resonant frequency as a function of capacitance (typical curve)



Max. RMS current as a function of frequency

### APPLICATION NOTES AND LIMITING CONDITIONS

- For X2 electromagnetic interference suppression in **standard across the line applications** (50 Hz / 60 Hz) with a maximum mains voltage of 310 V<sub>AC</sub>
- These capacitors are suitable for the application as voltage-division impedance in series with the mains (50 Hz / 60 Hz) with a maximum mains voltage of U<sub>RAC</sub>.
- To ensure withstanding high humidity requirements in the application the epoxy adhesion at the leads shall not be damaged. Therefore the leads may not be damaged or not be bent before soldering.
- For capacitors connected in parallel, normally the proof voltage and possibly the rated voltage must be reduced. For information depending of the capacitance value and the number of parallel connections contact [rfi@vishay.com](mailto:rfi@vishay.com).
- These capacitors are not intended for continuous pulse applications. For these situations, capacitors of the AC and pulse program must be used.
- The maximum ambient temperature must not exceed 110 °C.
- Rated voltage pulse slope:  
if the pulse voltage is lower than the rated voltage, the values of the specific reference data can be multiplied by 435 V<sub>DC</sub> and divided by the applied voltage.



INSPECTION REQUIREMENTS

General Notes

Sub-clause numbers of tests and performance requirements refer to the "Sectional Specification, Publication IEC 60384-14 ed-3 and Specific Reference Data".

GROUP C INSPECTION REQUIREMENTS		
SUB-CLAUSE NUMBER AND TEST	CONDITIONS	PERFORMANCE REQUIREMENTS
<b>SUB-GROUP C1A PART OF SAMPLE OF SUB-GROUP C1</b>		
4.1 Dimensions (detail)		As specified in Chapters "General data" of this specification
Initial measurements	Capacitance Tangent of loss angle: for C ≤ 1 µF at 10 kHz for C > 1 µF at 1 kHz	
4.3 Robustness of terminations	Tensile: load 10 N; 10 s Bending: load 5 N; 4 x 90°	No visible damage
4.4 Resistance to soldering heat	No pre-drying Method: 1A Solder bath: 280 °C ± 5 °C Duration: 10 s	
4.19 Component solvent resistance	Isopropylalcohol at room temperature Method: 2 Immersion time: 5 min ± 0.5 min Recovery time: min. 1 h, max. 2 h	
4.4.2 Final measurements	Visual examination	No visible damage Legible marking
	Capacitance	ΔC/C  ≤ 5 % of the value measured initially
	Tangent of loss angle	Increase of tan δ: ≤ 0.008 for: C ≤ 1 µF or ≤ 0.005 for: C > 1 µF Compared to values measured initially
	Insulation resistance	As specified in section "Insulation Resistance" of this specification
<b>SUB-GROUP C1B PART OF SAMPLE OF SUB-GROUP C1</b>		
Initial measurements	Capacitance Tangent of loss angle: for C ≤ 1 µF at 10 kHz for C > 1 µF at 1 kHz	
4.20 Solvent resistance of the marking	Isopropylalcohol at room temperature Method: 1 Rubbing material: cotton wool Immersion time: 5 min ± 0.5 min	No visible damage Legible marking
4.6 Rapid change of temperature	θA = -55 °C θB = +110 °C 5 cycles Duration t = 30 min	






GROUP C INSPECTION REQUIREMENTS		
SUB-CLAUSE NUMBER AND TEST	CONDITIONS	PERFORMANCE REQUIREMENTS
<b>SUB-GROUP C1B PART OF SAMPLE OF SUB-GROUP C1</b>		
4.6.1 Inspection	Visual examination	No visible damage
4.7 Vibration	Mounting: see section "Mounting" of this specification Procedure B4 Frequency range: 10 Hz to 55 Hz Amplitude: 0.75 mm or Acceleration 98 m/s <sup>2</sup> (whichever is less severe) Total duration 6 h	
4.7.2 Final inspection	Visual examination	No visible damage
4.9 Shock	Mounting: see section "Mounting" for more information Pulse shape: half sine Acceleration: 490 m/s <sup>2</sup> Duration of pulse: 11 ms	
4.9.2 Final measurements	Visual examination	No visible damage
	Capacitance	$ \Delta C/C  \leq 5\%$ of the value measured initially
	Tangent of loss angle	Increase of tan $\delta$ : $\leq 0.008$ for: $C \leq 1 \mu\text{F}$ or $\leq 0.005$ for: $C > 1 \mu\text{F}$ Compared to values measured initially
	Insulation resistance	As specified in section "Insulation Resistance" of this specification
<b>SUB-GROUP C1 COMBINED SAMPLE OF SPECIMENS OF SUB-GROUPS C1A AND C1B</b>		
4.11 Climatic sequence		
4.11.1 Initial measurements	Capacitance Measured in 4.4.2 and 4.9.2 Tangent of loss angle: measured initially in C1A and C1B	
4.11.2 Dry heat	Temperature: 110 °C Duration: 16 h	
4.11.3 Damp heat cyclic Test Db First cycle		
4.11.4 Cold	Temperature: -55 °C Duration: 2 h	
4.11.5 Damp heat cyclic Test Db remaining cycles		



GROUP C INSPECTION REQUIREMENTS		
SUB-CLAUSE NUMBER AND TEST	CONDITIONS	PERFORMANCE REQUIREMENTS
<b>SUB-GROUP C1 COMBINED SAMPLE OF SPECIMENS OF SUB-GROUPS C1A AND C1B</b>		
4.11.6 Final measurements	Visual examination  Capacitance  Tangent of loss angle  Voltage proof 1350 V <sub>DC</sub> 1 min between term.  Insulation resistance	No visible damage Legible marking  $ \Delta C/C  \leq 5\%$ of the value measured in 4.11.1.  Increase of tan $\delta$ : $\leq 0.008$ for: $C \leq 1 \mu\text{F}$ or $\leq 0.005$ for: $C > 1 \mu\text{F}$ Compared to values measured in 4.11.1.  No permanent breakdown or flash-over  $\geq 50\%$ of values specified in section "Insulation resistance" of this specification
<b>SUB-GROUP C2</b>		
4.12 Damp heat steady state	56 days; 40 °C; 90 % to 95 % RH no load	
4.12.1 Initial measurements	Capacitance Tangent of loss angle: 1 kHz	
4.12.3 Final measurements	Visual examination  Capacitance  Tangent of loss angle  Voltage proof 1350 V <sub>DC</sub> ; 1 min between terminations  Insulation resistance	No visible damage Legible marking  $ \Delta C/C  \leq 5\%$ of the value measured in 4.12.1.  Increase of tan $\delta$ : $\leq 0.008$ for: $C \leq 1 \mu\text{F}$ or $\leq 0.005$ for: $C > 1 \mu\text{F}$ Compared to values measured in 4.12.1.  No permanent breakdown or flash-over  $\geq 50\%$ of values specified in section "Insulation resistance" of this specification
<b>SUB-GROUP C2A</b>		
4.12A Damp heat steady state with load	RH: 85 %; Temp.: 85 °C; Load: 240 V <sub>AC</sub> Duration: 1000 h	
4.12.1A Initial measurements	Capacitance Tangent of loss angle: 1 kHz	
4.12.3A Final measurements	Visual examination  Capacitance  Tangent of loss angle  Voltage proof 1350 V <sub>DC</sub> ; 1 min between terminations.  Insulation resistance	No visible damage Legible marking  $ \Delta C/C  \leq 10\%$ of the value measured in 4.12.1A  Increase of tan $\delta$ : $\leq 0.015$ Compared to values measured in 4.12.1A  No permanent breakdown or flash-over  $\geq 50\%$ of values specified in section "Insulation resistance" of this specification



GROUP C INSPECTION REQUIREMENTS		
SUB-CLAUSE NUMBER AND TEST	CONDITIONS	PERFORMANCE REQUIREMENTS
<b>SUB-GROUP C3</b>		
4.13.1 Initial measurements	Capacitance Tangent of loss angle: for C ≤ 1 μF at 10 kHz for C > 1 μF at 1 kHz	
4.13 Impulse voltage	3 successive impulses, full wave, peak voltage: X2: 2.5 kV for C ≤ 1 μF X2: 2.5 kV/√C for C > 1 μF Max. 24 pulses Duration: 1000 h	No self healing breakdowns or flashover
4.14 Endurance	1.25 x U <sub>RAC</sub> at 110 °C Once in every hour the voltage is increased to 1000 V <sub>RMS</sub> for 0.1 s via resistor of 47 Ω ± 5 %	
4.14.7 Final measurements	Visual examination  Capacitance  Tangent of loss angle  Voltage proof 1350 V <sub>DC</sub> ; 1 min between terminations. 2120 V <sub>AC</sub> ; 1 min between terminations and case.  Insulation resistance	No visible damage Legible marking   ΔC/C  ≤ 10 % compared to values measured in 4.13.1.  Increase of tan δ: ≤ 0.008 for: C ≤ 1 μF or ≤ 0.005 for: C > 1 μF Compared to values measured in 4.13.1.  No permanent breakdown or flash-over  ≥ 50 % of values specified in section "Insulation resistance" of this specification
<b>SUB-GROUP C4</b>		
4.15 Charge and discharge	10 000 cycles Charged to 435 V <sub>DC</sub> Discharge resistance: $R = \frac{435 V_{DC}}{1.5 \times C(dU/dt)}$	
4.15.1 Initial measurements	Capacitance Tangent of loss angle: for C ≤ 1 μF at 10 kHz for C > 1 μF at 1 kHz	
4.15.3 Final measurements	Capacitance  Tangent of loss angle  Insulation resistance	ΔC/C  ≤ 10 % compared to values measured in 4.15.1.  Increase of tan δ: ≤ 0.008 for: C ≤ 1 μF or ≤ 0.005 for: C > 1 μF Compared to values measured in 4.15.1.  ≥ 50 % of values specified in section "Insulation resistance" of this specification

<b>GROUP C INSPECTION REQUIREMENTS</b>		
<b>SUB-CLAUSE NUMBER AND TEST</b>	<b>CONDITIONS</b>	<b>PERFORMANCE REQUIREMENTS</b>
<b>SUB-GROUP C5</b>		
4.16 Radio frequency characteristic	Resonance frequency	$\geq 0.9$ times the value as specified in section "Resonant frequency" of this specification.
<b>SUB-GROUP C6</b>		
4.17 Passive flammability Class B for Volume $> 1750 \text{ mm}^3$ Class C for Volume $\leq 1750 \text{ mm}^3$	Bore of gas jet: $\varnothing 0.5 \text{ mm}$ Fuel: butane Test duration for actual volume $V$ in $\text{mm}^3$ : $V \leq 250$ : 5 s $250 < V \leq 500$ : 10 s $500 < V \leq 1750$ : 20 s $V > 1750$ : 60 s One flame application  	After removing test flame from capacitor, the capacitor must not continue to burn for more than 30 s for $V \leq 1750 \text{ mm}^3$ and 10 s for $V > 1750 \text{ mm}^3$ . No burning particle must drop from the sample.
<b>SUB-GROUP C7</b>		
4.18 Active flammability	20 cycles of 2.5 kV discharges on the test capacitor connected to $U_{RAC}$	The cheese cloth around the capacitors shall not burn with a flame. No electrical measurements are required.



## **Disclaimer**

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.