






REVISIONS				
#	LY#	DESCRIPTION	DATE	OWN APVD
	D	REVISED PER ECO-16-009784	20JUN16	RS GJ



POS.	DIM. A
3*5	33.70
3*4	27.70
3*3	21.70









- ⚠ MATERIAL:
 LEVEL 1:PBT,STANDARD TEMPERATURE 105°C
 KEY A:NATURAL; KEY B:PURPLE; KEY C:BLUE; KEY D:YELLOW

 LEVEL 2:NYLON,HIGH TEMPERATURE 150°C
 KEY A:LIGHT GREY; KEY B:RED; KEY C:BLACK; KEY D:NATURAL
- ⚠ MATERIAL MARK:
 LEVEL 1:PBT,LEVEL 2:HDT
- 3 APPLICABLE CONTACT P/N
 RECEPTACLE CONTACT:1971237/1971779/81/83/85/87-*, 2238066-*
- 4 MATING CONN. P/N
 CAP HSG:*-1971874/5-*,
 DOUBLE ROW LOCK PLATE:*-1971778-*,SINGLE ROW LOCK PLATE:*-1971777-*

5 This product has not completed validation testing.

THIS DRAWING IS A CONTROLLED DOCUMENT.		OWN TOMMY WU 09JUL2012	TE Connectivity NAME PLUG HOUSING,TRIPLE ROW POWER TRIPLE LOCK
DIMENSIONS:		CHK HAPYE WU 09JUL2012	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD YUHONG MAO 09JUL2012	
mm		PRODUCT SPEC	
0 PLC	±	108-106118	SIZE
1 PLC	±0.35	APPLICATION SPEC	CAGE CODE
2 PLC	±0.25	114-106118	DRAWING NO
3 PLC	±	WEIGHT	RESTRICTED TO
4 PLC	±	Customer Drawing	A100779C=1971876
ANGLES	±	SCALE 3:1	SHEET 1 OF 2
FINISH	-	REV D	

REVISIONS				
P	LY#	DESCRIPTION	DATE	APPV
-	-	SEE SHEET 1	-	-




POS.	MATERIAL	KEY	P/N
3*5		LEVEL 1	KEY A 1-1971876-7
			KEY B 2-1971876-7
			KEY C 3-1971876-7
			KEY D 4-1971876-7
3*4		LEVEL 1	KEY A 5-1971876-7
			KEY B 6-1971876-7
			KEY C 7-1971876-7
			KEY D 8-1971876-7
3*3		LEVEL 1	KEY A 1-1971876-4
			KEY B 2-1971876-4
			KEY C 3-1971876-4
			KEY D 4-1971876-4
3*3		LEVEL 2	KEY A 5-1971876-4
			KEY B 6-1971876-4
			KEY C 7-1971876-4
			KEY D 8-1971876-4


3*3 POSITIONS

3*4 POSITIONS


3*5 POSITIONS



KEYING FOR 3*3 POS.



KEYING FOR 3*4 POS.



KEYING FOR 3*5 POS.

THIS DRAWING IS A CONTROLLED DOCUMENT.		OWN TOMMY WU 09JUL2012	TE Connectivity NAME PLUG HOUSING, TRIPLE ROW POWER TRIPLE LOCK
DIMENSIONS: mm		CHK HAPYE WU 09JUL2012	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APPV YUHONG MAO 09JUL2012	
0 PLC ± 1 PLC ±0.35 2 PLC ±0.25 3 PLC ± 4 PLC ± ANGLES FINISH ±		PRODUCT SPEC 108-106118 APPLICATION SPEC 114-106118 WEIGHT Customer Drawing	
SIZE CAGE CODE DRAWING NO. RESTRICTED TO A1 00779C=1971876 2 OF 2 REV D			

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[1-1971876-4](#)