









RoHS Compliant



Dimensions (In.)



■ SPECIFICATIONS

- Impedance variation: $\pm 10\%$ @ 1KHz
- DC Resistance tolerance: $\pm 15\%$
- Insulation: $>10M\Omega$ @ 100VDC
- Core type / size: EI-14
- Breakdown voltage: 100VAC Hipot for 1 minute
- Waxing: Vacuum treatment can be water washed with water temperature less than 20°C
- Max output: 75mW
- Freq. response: $\pm 3\text{dB}$, 300Hz-3.5 KHz @ 1KHz 0dB
- Can be water washed with water temperature less than 20°C
- RoHS Compliant

Mouser Stock No.	Impedance		Resistance	
	PRI	SEC	PRI	SEC
42XL001-RC	500 Ω	8 Ω	35 Ω	1 Ω
42XL002-RC	10K Ω	2K Ω	580 Ω	200 Ω
42XL003-RC	1.2K Ω	8 Ω	80 Ω	1 Ω
42XL009-RC	500 Ω	500 Ω	40 Ω	38 Ω
42XL016-RC	600 Ω	600 Ω	65 Ω	55 Ω
42XL031-RC	600 Ω	100 Ω	74 Ω	28 Ω

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Xicon:](#)

[42XL003-RC](#) [42XL031-RC](#) [42XL009-RC](#) [42XL001-RC](#) [42XL016-RC](#) [42XL002-RC](#)