## SPECIFICATION CONTROL DRAWING

**CHEMINAX** 

.0235

.055

.127

.157

(nominal)

.166

(maximum)

100 OHM, AWG 24, 19 STRANDS OF AWG 36, TWINAXIAL CABLE

	0024A0311
Date	2-21-13
Revision	G

THIS SPECIFICATION SHEET FORMS A PART OF THE LATEST ISSUE OF RAYCHEM SPECIFICATION 1200.

## CONSTRUCTION DETAILS

**ELECTRICAL CHARACTERISTICS** 

DIMENSIONS ARE NOMINAL VALUES IN INCHES UNLESS OTHERWISE

CONDUCTORS

AWG 24, 19 Strands of

AWG 36, Tin-Coated Copper

**DIELECTRICS** 

Ravfoam L

SHIELD

**JACKET** 

Thermorad S

AWG 38,

Tin-Coated Copper

Colors - White/Tan

CHARACTERISTIC IMPEDANCE MUTUAL CAPACITANCE VELOCITY OF PROPAGATION

100 ± 10 ohms, Method C at 1 MHz

13.5 pF/ft. (nominal) 79% (nominal)

## ADDITIONAL REQUIREMENTS

**ELECTRICAL** 

CONDUCTOR RESISTANCE 25.7 ohms/1000 ft. (nominal) INSULATION RESISTANCE 10,000 megohms (minimum)

for 1000 ft.

JACKET FLAWS

SPARK TEST 1.0 kV (rms) IMPULSE TEST 6.0 kV (peak)

VOLTAGE WITHSTAND (DIELECTRIC) 1000 volts (rms) (minimum)

**ENVIRONMENTAL** 

**FLAMMABILITY** Method C 225°C **HEAT SHOCK** 

LOW TEMPERATURE-COLD BEND -55°C/1.50 inch mandrel **VOLTAGE WITHSTAND** 1000 volts (rms),1 minute

(Post Environmental)

**PHYSICAL** 

INSULATION (DIELECTRIC)

(Prior to Cabling)

**ELONGATION** 50% (minimum) TENSILE STRENGTH 800 lbf/in2 (minimum)

JACKET

**ELONGATION** 

100% (minimum) TENSILE STRENGTH 2000 lbf/in2 (minimum) JACKET THICKNESS .015 inch (nominal)

SHIELD COVERAGE 90% (minimum)

Outer jacket color will be white (designated by a "-9" appended to the part number, e.g. 0024A0311-9) unless otherwise

Designate outer jacket color with a dash number in accordance with MIL-STD-681. Other codes and suffixes may be added to the part number, as necessary, to capture any additional requirements imposed by the purchase order.

WEIGHT 16.0 lbs/1000 ft. (nominal)

Users should evaluate the suitability of this product for their application. Specifications are subject to change without notice. Tyco Electronics Corporation also reserves the right to make changes in materials or processing, which do not affect compliance with any specification, without notification to Buyer.

Page 1 of 1

Rayfoam, Thermorad, Cheminax, Raychem, TE Connectivity, TE connectivity (logo) and TE (logo) are trademarks.



## **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

TE Connectivity: 0024A0311-0