

IEC Appliance Inlet C20 with Filter, Circuit Breaker TA45 (recessed)



Screw-on from front side
Rocker non-illuminated
white



Screw-on from front side
Rocker illuminated
orange



See below:
[Approvals and Compliances](#)

Description

- Panel mount :
Screw-on mounting from front side
- 3 Functions :
Appliance Inlet Protection class I , circuit breaker type TA45 2-pole
, Line filter in standard and medical version
- Quick connect terminals 6.3 x 0.8 mm

Characteristics

- All single elements are already wired
- Circuit Breaker non-illuminated or illuminated
- With EMC-shield
- For applications according IEC/UL 62368-1 we recommend variants with bleed resistor
Suitable for use in medical equipment according to IEC/UL 60601-1

Other versions on request

- Variant with notch for V-Lock mating Cordsets

References

Alternative: version without line filter [EF11](#)

Alternative: Standard version

Weblinks

[pdf data sheet](#), [html datasheet](#), [General Product Information](#), [Approvals](#), [Distributor-Stock-Check](#), [Accessories](#), [Detailed request for product](#), [Landing Page](#)

Technical Data

Ratings IEC	12 - 16A @ Ta 40 °C / 250VAC; 50Hz
Ratings UL/CSA	12 - 20A @ Ta 40 °C / 250VAC; 60Hz
Leakage Current	standard < 0.5mA (250 V / 60Hz) medical < 5 µA (250 V / 60 Hz)
Dielectric Strength	> 1.7 kVDC between L-N > 2.7 kVDC between L/N-PE Test voltage (2 sec)
Allowable Operation Temperature	-10 °C to 55 °C
Climatic Category	10/055/21 acc. to IEC 60068-1
IP-Protection	from front side IP40 acc. to IEC 60529
Protection Class	Suitable for appliances with protection class I acc. to IEC 61140
Terminal	Quick connect terminals 6.3 x 0.8 mm
Panel Thickness S	Screw: max 8 mm Mounting screw torque max 0.5 Nm
Material: Housing	Thermoplastic, black, UL 94V-0

Appliance inlet/-outlet	C20 acc. to IEC 60320-1, UL 498, CSA C22.2 no. 42 (for cold conditions) pin-temperature 70 °C, 16A, Protection Class I
Circuit Breakers	Acc. IEC/EN 60934, UL 1077, CSA 22.2 no. 235 2-pole rocker switch, illuminated or non-illuminated. Optional with undervoltage- or remote trip release Short circuit capacity Icn: at In < 3A/240VAC : 10 x In at In ≥ 3A/240VAC : 300A
Line Filter	Standard and Medical Version, IEC 60939, UL 1283, CSA C22.2 no. 8 Technical Details
MTBF	> 100'000h acc. to MIL-HB-217 F

Approvals and Compliances



Detailed information on product approvals, code requirements, usage instructions and detailed test conditions can be looked up in [Details about Approvals](#)

SCHURTER products are designed for use in industrial environments. They have approvals from independent testing bodies according to national and international standards. Products with specific characteristics and requirements such as required in the automotive sector according to IATF 16949, medical technology according to ISO 13485 or in the aerospace industry can be offered exclusively with customer-specific, individual agreements by SCHURTER.

Approvals








The approval mark is used by the testing authorities to certify compliance with the safety requirements placed on electronic products.

Approval Reference Type: EF12

Approval Logo	Certificates	Certification Body	Description
	VDE Approvals	VDE	Certificate Number: 40001520
	UL Approvals	UL	UL File Number: E72928



Product standards

Product standards that are referenced

Organization	Design	Standard	Description
	Designed according to	IEC 60320-1	Appliance couplers for household and similar general purposes
	Designed according to	IEC 60939	Passive filters for suppressing electromagnetic interference
	Designed according to	IEC 61058-1	Switches for appliances. Part 1. General requirements
	Designed according to	UL 498	Standard for Attachment Plugs and Receptacles
	Designed according to	UL 1283	Electromagnetic interference filters
	Designed according to	CSA C22.2 no. 42	General Use Receptacles, Attachment Plugs, and Similar Wiring Devices
	Designed according to	CSA C22.2 no. 8	Electromagnetic interference (EMI) filters







Application standards

Application standards where the product can be used


Organization	Design	Standard	Description
	Designed for applications acc.	IEC/UL 62368-1	IEC 62368-1 includes the basic requirements for safety of audio, video, information technology and office equipment.
	Designed for applications acc.	IEC 60601-1	Medical electrical equipment - Part 1: General requirements for basic safety and essential performance

Compliances

The product complies with following Guide Lines

Identification	Details	Initiator	Description
	CE declaration of conformity	SCHURTER AG	The CE marking declares that the product complies with the applicable requirements laid down in the harmonisation of Community legislation on its affixing in accordance with EU Regulation 765/2008.
	RoHS	SCHURTER AG	Directive RoHS 2011/65/EU, Amendment (EU) 2015/863
	China RoHS	SCHURTER AG	The law SJ / T 11363-2006 (China RoHS) has been in force since 1 March 2007. It is similar to the EU directive RoHS.
	REACH	SCHURTER AG	On 1 June 2007, Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorization and Restriction of Chemicals 1 (abbreviated as "REACH") entered into force.
	Landing Page V-Lock	SCHURTER AG	V-Lock system are based on a matching plug-dose combination. The connector is equipped with a notch intended for use with the latching cordset. The cord latching system prevents against accidental removal of the cordset.
	Medical Technology	SCHURTER AG	Suitable for use in medical equipment according to IEC/UL 60601-1

Dimension [mm]




* --- Version TA45 with undervoltage release

Technical Data of Filter-Components

Rated Current [A]	Filter-Type	Inductances L [mH]	Capacitance CX [nF]	Capacitance CY [nF]	R [M Ω]
12	Standard version	2 x 0.8	100	2.2	1
16	Standard version	2 x 0.6	100	2.2	1
20	Standard version	2 x 0.3	100	2.2	1
12	Medical Version (M5)	2 x 0.8	100	-	1
16	Medical Version (M5)	2 x 0.6	100	-	1
20	Medical Version (M5)	2 x 0.3	100	-	1


Diagrams

Standard version



1) Line
2) Load

Medical Version (M5)




1) Line
2) Load


Attenuation Loss

Standard version


12 A



16 A




20 A




Medical version (M5)


12 A



16 A



20 A



Effect of ambient temperature


The units are calibrated for an ambient temperature of +23°C. To determine the rated current for a lower or higher ambient temperature, use a correction factor (typical value) from the table below:

Ambient Temperature [°C]	Correction factor
-10	0.89
-5	0.91
0	0.92
+23	1.00
+30	1.03
+40	1.08
+55	1.16


Example: Rated current = 5 A, Environmental temperature = 40 °C, --> Correction factor = 1.08, Resulting current = 5.5 A --> Fount to next higher rated current: 6 A

Time-Current-Curves


Tripping Characteristics $I_n < 3 \text{ A}$



Tripping Characteristics $I_n \geq 3 \dots < 18 \text{ A}$




Tripping Characteristics $I_n \geq 18 \text{ A}$



Configuration code TA45


Type	Configuration code TA45											
EF12	A	3	2	6	M	1	5	0	C	0	000	2131-10-00



- Circuit Breaker of Equipment
- 2-pole, rocker actuated
- Quick connect terminal
- Other types on request


Without release: code C0

Undervoltage release



•	•	•
•	•	•
•	•	•

Remote trip release



Code	Rated voltage U _N
2	240 V AC
3	230 V AC
4	120 V AC

Rated current circuit breaker of equipment


I _n	Code	I _n	Code	I _n	Code	I _n	Code
10,0	100	13,0	130	16,0	160	19,0	190
11,0	110	14,0	140	17,0	170	20,0	200
12,0	120	15,0	150	18,0	180		

Other rated currents on request

Rocker legend

Surface	Illustration	Colour of print
F embossed	— ○	
H printed	ON OFF	white
K printed	ON OFF	black
L printed	— ○	white
M printed	— ○	black
P printed	I ○	white
R printed	I ○	black

Position of the rocker legend e.g F




Colours

Switch front	Rocker
W black	white
B black	black
6 black	— orange transp.

Diagram

Thermal overload protection



Without illumination


ABT ABD

With illumination 220...240 V
110...120 V

A12 A32
A14 A34

Configuration code (Order example)

Type	Configuration code TA45													
EF12	A	3	2	6	M	1	5	0	C	0	-	000	-	2131-10-00



The rated current of the line-filter must not be exceeded in the end application.

Variants

Circuit Breakers				Filter		Connectors		Internally wired	Config. Code	Order Number
Rated Current [A]	Rocker colour	Illumination	Add-on modules	Rated Current [A]	Filter Type	Protection Class	V-Lock			
12	black	non-illuminated	-	12	Standard version	I		prewired	EF12.ABDWF120C0.3110.01	EF12.1034.3110.01
15	black	non-illuminated	-	20	Standard version	I		prewired	EF12.ABDBL150C0.1110.01	EF12.1089.1110.01
15	black	non-illuminated	-	16	Standard version	I		prewired	EF12.ABDWF150C0.2110.01	EF12.0885.2110.01
16	black	non-illuminated	-	16	Standard version	I		prewired	EF12.ABDBL160C0.2110.01	EF12.2105.2110.01
16	black	non-illuminated	-	16	Standard version	I		prewired	EF12.ABDWF160C0.2110.01	EF12.0699.2110.01
16	black	non-illuminated	-	16	Standard version	I		prewired	EF12.ABTBP160C0.2110.01	EF12.3103.2110.01
16	black	non-illuminated	-	16	Standard version	I		prewired	EF12.ABTWF160C0.2110.01	EF12.0034.2110.01
20	black	non-illuminated	-	20	Standard version	I		prewired	EF12.A126K200C0.1110.01	EF12.3197.1110.01
20	black	non-illuminated	-	20	Standard version	I		prewired	EF12.A326K200C0.1110.01	EF12.2561.1110.01
20	black	non-illuminated	-	20	Standard version	I		prewired	EF12.ABDBL200C0.1110.01	EF12.2196.1110.01
20	black	non-illuminated	-	20	Standard version	I		prewired	EF12.ABDWF200C0.1110.01	EF12.0572.1110.01
20	black	non-illuminated	-	20	Standard version	I		prewired	EF12.ABDWM200C0.1110.01	EF12.2961.1110.01
20	black	non-illuminated	-	20	Standard version	I		prewired	EF12.ABTWF200C0.1110.01	EF12.0035.1110.01
20	black	non-illuminated	-	20	Standard version	I		prewired	EF12.ABTWF200U2.1110.01	EF12.1164.1110.01
16	black	non-illuminated	-	16	Medical Version (M5)	I		prewired	EF12.ABDWF160C0.2210.01	EF12.0699.2210.01
20	black	non-illuminated	-	20	Medical Version (M5)	I		prewired	EF12.ABTWF200C0.1210.01	EF12.0035.1210.01

Most Popular.

Availability for all products can be searched real-time:<https://www.schurter.com/en/Stock-Check/Stock-Check-SCHURTER>

Packaging unit16 Pcs

Accessories

Description



Cord retaining kits
Cord retaining strain relief

Flat head, H

4700.0008

Mating Outlets/Connectors

Category / Description



[Connector Overview complete](#)

4795, Mounting: Power Cord, Cable Connector: IEC C19	4795
4790, Mounting: Power Cord, Screw Connector: IEC C19	4790
0104U, Mounting: Power Supply Cord, Screw clamps Connector: IEC C19	0104U

[Connector further types to EF12](#)

Mating Outlets/Connectors shuttered



[Power Cord Overview complete](#)

VAC19KS, Overview, V-Lock cord retaining, diverse Connector IEC C19, diverse, black	VAC19KS
---	---------

[Power Cord further types to EF12](#)

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Schurter:

[EF12.ABDBL150C0.1110.01-20A-S](#) [EF12.0699.211001](#) [EF12.ABDBL100C0.2110.01](#) [EF12.ABDWF200C0.1110.01-20A-S](#) [EF12.ABDWF150C0.2110.01-16A-S](#) [EF12.ABTWF160C0.2110.01-16A-S](#) [EF12.ABTWF200C0.1110.01-20A-S](#)
[EF12.0035.1210.01](#) [EF12.0699.2110.01](#) [EF12.0699.2210.01](#) [EF12.1164.1110.01](#) [EF12.2078.1110.01](#)
[EF12.2105.1110.01](#) [EF12.2105.1110.02](#) [EF12.2105.2110.01](#) [EF12.2105.2210.01](#) [EF12.2196.1110.01](#)
[EF12.2561.1110.01](#) [EF12.2961.1110.01](#) [EF12.3103.2110.01](#) [EF12.3197.1110.01](#) [EF12.0034.2110.01](#)
[EF12.0035.1110.01](#) [EF12.0572.1110.01](#) [EF12.0861.1110.01](#) [EF12.0885.2110.01](#) [EF12.0924.1210.01](#)
[EF12.1034.3110.01](#) [EF12.1089.1110.01](#) [EF12.1511.2110.01](#) [EF12.1563.2110.01](#) [EF12.1894.1110.01](#)
[EF12.1894.1210.01](#) [EF12.2115.1110.01](#) [EF12.2183.1110.01](#) [EF12.0572.1210.01](#) [EF12.2420.3110.01](#)
[EF12.0470.2110.01](#) [EF12.0470.3110.01](#) [EF12.1250.1110.01](#) [EF12.2078.2110.01](#) [EF12.1250.3110.01](#)
[EF12.3353.2110.01](#) [EF12.3928.1210.01](#) [3-101-637](#) [3-104-419](#) [EF12.2105.1111.01](#) [EF12.0572.1211.01](#) [EF12-ABTWM200C0-000-1111-00-00](#)