

LOC	DIST	REVISIONS					
		P	LTR	DESCRIPTION	DATE	OWN	APVD
AD	00		B2	REVISED PER ECO-11-004587	11MAR11	RK	HMR

D







FIG 1



CONTENT ARRANGEMENT



C

B






FIG 2



A

1. FOR ADDITIONAL SPECIFICATIONS SEE AMP PRODUCT SPEC 108-7519.
2. SWITCH SHOWN IN OPEN POSITION.
3. ALL CHARACTERS AND ROCKERS ARE WHITE, HOUSING IS BLACK.
4. STAMPING WILL VARY ON 2 AND 3 POSITION TOPS DUE TO SPACE RESTRICTIONS.
5. STRIPPABLE TRANSPARENT SEAL, SEE FIG 6.
6. .315 DIMENSION APPLIES AT TERMINAL TIPS. TERMINALS ARE .300±.010 AT MOUNTING SURFACE.
7. NO POSITION MARKING.
8. NO PART NO. MARKING.
9. STRIPPABLE TAPE SEAL, SEE FIGURE 8.
10. ALL MATERIALS AND FINISHES SHALL COMPLY WITH EU DIRECTIVE 2002/95/EC OF 27JAN2003 (ROHS)
11. MATERIAL: HOUSING AND ROCKERS - POLYESTER
CONTACT & SOLDER LEAD - COPPER ALLOY
12. FINISH: CONTACT - GOLD OVER NICKEL
SOLDER LEAD - TIN OVER NICKEL
13. OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

13 OBSOLETE	FIG 2	FIG 3A& 7	1.08	10	6-5435802-3
	FIG 1	FIG 3B	.88	8	3-5435802-8
	FIG 2	7 8 5	.88	8	3-5435802-0
	FIG 2	7 8 5	.48	4	2-5435802-9
	FIG 2	FIG 3A 5	1.28	12	2-5435802-2
	FIG 2		1.18	11	2-5435802-1
	FIG 2		1.08	10	2-5435802-0
	FIG 2		.98	9	1-5435802-9
	FIG 2		.78	7	1-5435802-8
	FIG 2		.68	6	1-5435802-7
13 OBSOLETE	FIG 2		.58	5	1-5435802-6
	FIG 2	8	.48	4	1-5435802-5
	FIG 2	FIG 3A 8	1.28	12	1-5435802-2
	FIG 1	8	.28	2	1-5435802-0
	FIG 2	FIG 3A 5	.88	8	5435802-9
	FIG 2		1.08	10	5435802-8
	FIG 2		.98	9	5435802-7
	FIG 2		.78	7	5435802-6
	FIG 2		.68	6	5435802-5
	FIG 2		.58	5	5435802-4
5435802-1 SHOWN	FIG 2	8 8	.48	4	5435802-3
	FIG 2	8 8	.38	3	5435802-2
	FIG 2	FIG 3A	.88	8	5435802-1
	HOUSING	MARKING	PROT-ECTIVE SEAL	A	NO OF POSN
	PART NO				

LOC	DIST	REVISIONS					
		P	LTR	DESCRIPTION	DATE	DWN	APVD
AD	00		-	SEE SHEET 1	-	-	-




FIG 3A




FIG 3B





FIG 4



PROTECTIVE SEAL

FIG 6





FIG 7



PROTECTIVE SEAL

FIG 8

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN R. TALLEY 19-9-89	 TE Connectivity				
DIMENSIONS: INCHES		CHK R. MILLER 19-9-89					
	TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD H. LEITER 19-9-89	NAME SWITCH ASSY, DIP, TYPE C, 7000 SERIES, SPST, SIDE ACTUATED —			
	0 PLC ± — 1 PLC ± — 2 PLC ± — 3 PLC ± .005 4 PLC ± — ANGLES ± —		PRODUCT SPEC —				
	MATERIAL		APPLICATION SPEC —	SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
	SEE SHEET 1	FINISH	WEIGHT —	A2	00779	C-5435802	—
CUSTOMER DRAWING			SCALE 4:1		SHEET 2 OF 2		REV B2

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[1-5435802-8](#)