

Special function module - EEM-MEMO-MA600 - 2901370

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Storage module for intermediate storage of values for EEM-MA600



Product Features

- Stores the last ten alarms together with the time and date
- Stores the real and reactive power, e.g., for 31 days with a ten-minute synchronization pulse

Key Commercial Data

Packing unit	1 pc
Weight per Piece (excluding packing)	140.0 g
Custom tariff number	90303100
Country of origin	Hungary

Technical data

Note

Utilization restriction	EMC: class A product, see manufacturer's declaration in the download area
-------------------------	---

Dimensions

Width	22.5 mm
Height	65 mm
Depth	48 mm

Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-10 °C ... 55 °C (14 °F to 131 °F)
Ambient temperature (storage/transport)	-20 °C ... 85 °C (-4 °F ... 185 °F)
Max. permissible relative humidity (operation)	≤ 95 %
Max. salt spray content	≤ 2.5 %

Input data

Description of the input	Optocoupler input
--------------------------	-------------------

Special function module - EEM-MEMO-MA600 - 2901370

Technical data

Input data

Number	1
Voltage input signal	10 V DC ... 30 V DC
Input pulse length	≥ 1 s
Peak offstate voltage	30 V DC
Memory size	512 kByte

General

Supply voltage	9 V (via EEM-MA600)
Color	black
Conformance	CE-compliant
Rated insulation voltage at mains voltage < 300 V AC (L/N)	III
Rated insulation voltage at mains voltage > 300 V AC - 600 V AC (L/N)	II
Test voltage	3.5 kV AC (50 Hz, 1 min.)

Connection data

Conductor cross section flexible min.	0.5 mm ²
Conductor cross section flexible max.	2.5 mm ²
Conductor cross section solid min.	0.5 mm ²
Conductor cross section solid max.	2.5 mm ²
Conductor cross section AWG min.	20
Conductor cross section AWG max.	14
Connection method	COMBICON plug-in screw terminal block
Stripping length	6 mm
Tightening torque	0.4 Nm

Standards and Regulations

Conformance	CE-compliant
UL, USA / Canada	UL 61010-1
	CSA-C22.2 No. 61010-1
	cULus

Classifications

eCl@ss

eCl@ss 4.0	27210902
eCl@ss 4.1	27371105
eCl@ss 5.0	27371801
eCl@ss 5.1	27371801
eCl@ss 6.0	27371801

Special function module - EEM-MEMO-MA600 - 2901370

Classifications

eCl@ss

eCl@ss 7.0	27371801
eCl@ss 8.0	27242212

ETIM

ETIM 3.0	EC001505
ETIM 4.0	EC000192
ETIM 5.0	EC000192

UNSPSC

UNSPSC 6.01	30211916
UNSPSC 7.0901	39121535
UNSPSC 11	39121535
UNSPSC 12.01	39121535
UNSPSC 13.2	39121535

Approvals

Approvals

Approvals

UL Listed / cUL Listed / EAC / EAC / cULus Listed

Ex Approvals

Approvals submitted

Approval details

UL Listed 

cUL Listed 
--

Special function module - EEM-MEMO-MA600 - 2901370

Approvals

EAC

EAC

cULus Listed 

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Phoenix Contact:](#)

[2901370](#)