


LOC	DIST	REVISIONS						
CM	00	P	LTR	DESCRIPTION	DATE	DWN	APVD	
			J	REVISED PER ECO-06-008105	01SEP2006	KW	DB	
			K	ECO-07-018581	11OCT2007	KW	DB	
			K1	ECO-07-030039	23JAN2008	KW	DB	
			K2	REVISED PER ECO-09-025699	11DEC09	KK	AEG	

- △ POST TO WITHSTAND 13 NEWTONS (3 LBS) MIN AXIAL FORCE IN BOTH DIRECTIONS SHOWN WITHOUT DISLODGING.
- △ TOLERANCES APPLY TO SOLDER SIDE OF BOARD.
- △ MEASURED AT -A-.
4. PARTS TO COMPLY WITH AMP SOLDERABILITY SPEC 109-11-2.
- △ ONE HOLE MAY BE UNDERSIZED 0.81 - 0.89 [.032 - .035] DIA. FOR ASSEMBLY RETENTION DURING WAVE SOLDERING.
- △ MATERIAL: HOUSING : NYLON, 4/6, HIGH TEMP, BLACK.
POST -2 THRU -12 :COPPER ALLOY TIN LEAD (93/7) PLATING
POST -32 THRU -42 : COPPER ALLOY TIN PLATE
- △ COORDINATE DIMENSION APPLIES FROM CENTER OF ACTUAL FEATURE.
- △ POST TO BE MEASURED WHEN STRIP IS HELD FLAT.
9. TUBE MUST MAINTAIN PART ORIENTATION AND ALLOW FREE SLIDING AT A 45° TUBE INCLINE.
10. DIMENSIONS IN BRACKETS ARE IN INCHES.
- △ AMP LOGO AND UL AND CSA TRADEMARKS TO APPEAR ON THIS SURFACE.
- △ OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI



TUBE LOADED HEADER ASSEMBLY

△12	SUPERCEDED BY 4-647295-2	TIN-LEAD	7.62 [.300]	12.70 [.500]	2	19	30.48 [1.200]	12	4-647295-2
	SUPERCEDED BY 4- -1	TIN-LEAD	-	10.16 [.400]	2	20	27.94 [1.100]	11	4-647295-1
	SUPERCEDED BY 4- -0	TIN-LEAD	-	7.62 [.300]	2	22	25.40 [1.000]	10	4-647295-0
	SUPERCEDED BY 3- -9	TIN-LEAD	-	5.08 [.200]	2	25	22.86 [.900]	9	3-647295-9
	SUPERCEDED BY 3- -8	TIN-LEAD	-	2.54 [.100]	2	28	20.32 [.800]	8	3-647295-8
	SUPERCEDED BY 3- -7	TIN-LEAD	-	-	2	32	17.78 [.700]	7	3-647295-7
	SUPERCEDED BY 3- -6	TIN-LEAD	-	-	2	38	15.24 [.600]	6	3-647295-6
	SUPERCEDED BY 3- -5	TIN-LEAD	-	-	2	45	12.70 [.500]	5	3-647295-5
	SUPERCEDED BY 3- -4	TIN-LEAD	-	-	2	57	10.16 [.400]	4	3-647295-4
	SUPERCEDED BY 3- -3	TIN-LEAD	-	-	2	76	7.62 [.300]	3	3-647295-3
	SUPERCEDED BY 3-647295-2	TIN-LEAD	-	-	2	114	5.08 [.200]	2	3-647295-2
FINISH		W	G	PLUG	HEADER ASSEMBLIES	L	NO. OF POSN	TUBE LOADED ASSEMBLY PART NUMBER	
				QTY PER TUBE					

THIS DRAWING IS UNPUBLISHED. IT IS THE PROPERTY OF TYCO ELECTRONICS CORPORATION. IT IS TO BE USED ONLY FOR THE PURPOSES SPECIFIED IN THE ORDER. IT IS TO BE RETURNED TO TYCO ELECTRONICS CORPORATION WHEN NO LONGER REQUIRED. IT IS NOT TO BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, INCLUDING PHOTOCOPYING, RECORDING, OR BY ANY INFORMATION STORAGE AND RETRIEVAL SYSTEM. VIOLATION OF THIS NOTICE IS SUBJECT TO PROSECUTION AND DAMAGES WILL BE AWARDED.

DIMENSIONS: mm [INCHES]

TOLERANCES UNLESS OTHERWISE SPECIFIED:
9 PLC ±
1 PLC ±
2 PLC ±0.13 [1.005]
3 PLC ±
4 PLC ±
ANGLES ±0° 30'

MATERIAL

FINISH

DWN: R. WHITAKER 02JAN2002
CHK: D. BOSSI 02JAN2002
APVD: D. BOSSI 02JAN2002

NAME: MTA-100 HEADER ASSY, HIGH TEMP, FRICTION LOCK, .025 SQ STR POST, TIN OR TIN-LEAD PLATED, TUBE LOADED

PRODUCT SPEC

APPLICATION SPEC

SIZE: A11 CAGE CODE: 00779 DRAWING NO: C=647295

WEIGHT: -






CUSTOMER DRAWING

Tyco Electronics Corporation
Harrisburg, PA 17105-3608

RESTRICTED TO

SCALE: 5:1 SHEET: 1 OF 2 REV: K2

LOC		DIST		REVISIONS				
CM	00	P	LTR	DESCRIPTION	DATE	DWN	APVD	
		-	-	SEE SHEET 1	-	-	-	



RECOMMENDED MOUNTING HOLE PATTERN
FOR 1.57 ± 0.20 [0.062 ± 0.008] THICK P.C. BOARD



THIS DRAWING IS UNPUBLISHED. IT IS THE PROPERTY OF TYCO ELECTRONICS CORPORATION. IT IS TO BE USED ONLY FOR THE PURPOSES SPECIFIED IN THE ORDER. IT IS NOT TO BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, INCLUDING PHOTOCOPYING, RECORDING, OR BY ANY INFORMATION STORAGE AND RETRIEVAL SYSTEM. WITHOUT PERMISSION IN WRITING FROM TYCO ELECTRONICS CORPORATION.		DWN R. WHITAKER 02JAN2002	Tyco Electronics Corporation Harrisburg, PA 17105-3608	
DIMENSIONS: mm [INCHES]		CHK D. BOSSI 02JAN2002	NAME MTA-100 HEADER ASSY, HIGH TEMP, FRICTION LOCK, .025 SQ STR POST, TIN OR TIN-LEAD PLATED, TUBE LOADED	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD D. BOSSI 02JAN2002	PRODUCT SPEC	
0 PLC ±			APPLICATION SPEC	
1 PLC ±			WEIGHT	
2 PLC ±			CUSTOMER DRAWING	
3 PLC ±			SCALE 5:1	
4 PLC ±			SHEET 2 OF 2	
ANGLES ±0° 30'			REV K2	
FINISH				

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[3-647295-4](#)