

XY2CE1A297

e-stop rope pull switch XY2CE - RH side - 2NC
+2NO - pilot light 230V - boot. pb

Product availability: Non-Stock - Not normally stocked in distribution facility



Main

| | |
|-------------------------------|--|
| Commercial Status | Commercialised |
| Range of product | Preventa XY2 |
| Product or component type | Latching emergency stop rope pull switch |
| Device short name | XY2CE |
| Local signalling | With pilot light |
| Number of cables | 1 |
| Trigger cable maximum length | 229.66 ft (70 m) |
| Housing colour | Red RAL 3000 |
| Reset | By booted pushbutton |
| [Us] rated supply voltage | 230 V |
| Contacts type and composition | 2 NO + 2 NC |
| Trigger cable anchor point | RH side |
| Light block supply | Direct |
| Connections - terminals | Screw clamp terminal 1 x 0.5...2 x 1.5 mm ² |

Complementary

| | |
|--|---|
| Contacts operation | Slow-break |
| Tightening torque | 7.08...10.62 lbf.in (0.8...1.2 N.m) |
| Cable entry number | 3 plain hole for Pg 13.5 or ISO M20 cable gland |
| Mechanical durability | 10000 cycles |
| Distance between cable supports | 16.4 ft (5 m) |
| [Ie] rated operational current | 0.1 A at 250 V DC-13, R300 conforming to EN/IEC 60947-5-1 appendix A 0.75 A at 240 V AC-15, C300 conforming to EN/IEC 60947-5-1 appendix A |
| [Ithe] conventional enclosed thermal current | 10 A |
| [Ui] rated insulation voltage | 300 V conforming to CSA C22.2 No 14 400 V, degree of pollution: 3 conforming to EN/IEC 60947-1 300 V conforming to UL 508 |
| [Uimp] rated impulse withstand voltage | 4 kV |
| Positive opening | With conforming to EN/IEC 60947-5-1 |
| Resistance across terminals | <= 25 MOhm conforming to NF C 93-050 method A <= 25 MOhm conforming to EN/IEC 60255-7 category 3 |
| Short circuit protection | 6 A cartridge fuse, gG conforming to EN/IEC 60269 |
| Height | 5.59 in (142 mm) |
| Width | 9.02 in (229 mm) |
| Depth | 4.13 in (105 mm) |
| Terminals description ISO n°1 | (13-14)NO (21-22)NC |
| Product weight | 3.24 lb(US) (1.47 kg) |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

| | |
|---------------------------------------|--|
| Standards | EN/IEC 60947-5-1 EN/IEC 60947-5-5 EN/ISO 13850 UL 508 Machinery directive 2006/42/EC Work equipment directive 2009/104/EC |
| Safety level | Can reach SIL 3 conforming to EN/IEC 61508 Can reach category 4 conforming to EN/ISO 13849-1 (with the appropriate monitoring system and correctly wired) Can reach PL = e conforming to EN/ISO 13849-1 (with the appropriate monitoring system and correctly wired) |
| Safety reliability data | B10d = 50000 (value given for a life time of 20 years limited by mechanical or contact wear) |
| Protective treatment | TC |
| Ambient air temperature for operation | -13...158 °F (-25...70 °C) |
| Ambient air temperature for storage | -40...158 °F (-40...70 °C) |
| Vibration resistance | 10 gn (f = 10...300 Hz) conforming to EN/IEC 60068-2-6 |
| Shock resistance | 50 gn (11 ms) conforming to EN/IEC 60068-2-27 |
| IP degree of protection | IP65 |

Ordering and shipping details

| | |
|-----------------------|---|
| Category | 22441 - LIMIT SWITCHES,CABLE PULL |
| Discount Schedule | T |
| GTIN | 00785901638292 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 3.70 |
| Product availability | Non-Stock - Not normally stocked in distribution facility |
| Returnability | N |
| Country of origin | MA |

Offer Sustainability

| | |
|----------------------------------|---|
| Sustainable offer status | Not Green Premium product |
| RoHS | Compliant - since 0852 - Schneider Electric declaration of conformity |
| Product environmental profile | Available Download Product Environmental |
| Product end of life instructions | Need no specific recycling operations |

Contractual warranty

| | |
|--------|-----------|
| Period | 18 months |
|--------|-----------|

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Schneider Electric:](#)

[XY2CE1A297](#)