

	DESIGNED FOR USE WITH RG-58/U	REVISIONS																																																																														
	CABLE ENTRY DIAMETER MINIMUM	REV	DESCRIPTION	DATE	APPROVED																																																																											
	FERRULE	.202	010	RELEASED	3/13/97																																																																											
	CONTACT	.023 SLOT																																																																														
	HOUSING	.121																																																																														
	<table><tr><td>HOUSING COUPLING NUT CAP</td><td>STAINLESS STEEL PER ASTM-A484 AND ASTM- A582, TYPE 303</td><td>PASSIVATE PER QQ-P-35</td></tr><tr><td>DIELECTRIC</td><td>TFE FLUOROCARBON PER ASTM-D-1457</td><td>N/A</td></tr><tr><td>CENTER CONTACT</td><td>BERYLLIUM COPPER PER ASTM-B-196 OR ASTM-B-197, ALLOY C17300, CONDITION H</td><td>GOLD PLATE PER MIL-G-45204</td></tr><tr><td>RETAINING RING</td><td>BERYLLIUM COPPER PER ASTM-B-194, ALLOY C17200, CONDITION H</td><td>N/A</td></tr><tr><td>GASKET</td><td>SILICONE RUBBER PER ZZ-R-765</td><td>N/A</td></tr><tr><td>SHRINK TUBING</td><td>HEAT SHRINKABLE POLYOLEFIN COMPOUND MIL-I-23053/4</td><td>N/A</td></tr><tr><td>FERRULE</td><td>COPPER OR BRASS ALLOY ROCKWELL F65 MAXIMUM</td><td>GOLD PLATE PER MIL-G-45204</td></tr></table>					HOUSING COUPLING NUT CAP	STAINLESS STEEL PER ASTM-A484 AND ASTM- A582, TYPE 303	PASSIVATE PER QQ-P-35	DIELECTRIC	TFE FLUOROCARBON PER ASTM-D-1457	N/A	CENTER CONTACT	BERYLLIUM COPPER PER ASTM-B-196 OR ASTM-B-197, ALLOY C17300, CONDITION H	GOLD PLATE PER MIL-G-45204	RETAINING RING	BERYLLIUM COPPER PER ASTM-B-194, ALLOY C17200, CONDITION H	N/A	GASKET	SILICONE RUBBER PER ZZ-R-765	N/A	SHRINK TUBING	HEAT SHRINKABLE POLYOLEFIN COMPOUND MIL-I-23053/4	N/A	FERRULE	COPPER OR BRASS ALLOY ROCKWELL F65 MAXIMUM	GOLD PLATE PER MIL-G-45204																																																						
HOUSING COUPLING NUT CAP	STAINLESS STEEL PER ASTM-A484 AND ASTM- A582, TYPE 303	PASSIVATE PER QQ-P-35																																																																														
DIELECTRIC	TFE FLUOROCARBON PER ASTM-D-1457	N/A																																																																														
CENTER CONTACT	BERYLLIUM COPPER PER ASTM-B-196 OR ASTM-B-197, ALLOY C17300, CONDITION H	GOLD PLATE PER MIL-G-45204																																																																														
RETAINING RING	BERYLLIUM COPPER PER ASTM-B-194, ALLOY C17200, CONDITION H	N/A																																																																														
GASKET	SILICONE RUBBER PER ZZ-R-765	N/A																																																																														
SHRINK TUBING	HEAT SHRINKABLE POLYOLEFIN COMPOUND MIL-I-23053/4	N/A																																																																														
FERRULE	COPPER OR BRASS ALLOY ROCKWELL F65 MAXIMUM	GOLD PLATE PER MIL-G-45204																																																																														
<table><tr><td>ELECTRICAL</td><td>MECHANICAL</td><td>ENVIRONMENTAL</td></tr><tr><td>Nominal Impedance (Ohms) 50</td><td>Interface Dimensions MIL-STD-348A, Fig. 310.1</td><td>Temperature Rating -65°C to +165°C</td></tr><tr><td>Frequency Range (MHz) DC TO 12,400</td><td>Recommended Mating</td><td>Vibration MIL-STD-202, Method 204, Condition D</td></tr><tr><td>Volt Rating (VRMS MAX)</td><td>Torque 7-10 In-Lbs</td><td>Shock MIL-STD-202, Method 213, Condition I</td></tr><tr><td>Sea Level 335</td><td>Mating Characteristics:</td><td>Thermal Shock MIL-STD-202, Method 107, Condition B, Except High Temp +85°C</td></tr><tr><td>VSWR 1.15+-.02f(GHz)</td><td>Insertion (MAX Lbs) N/A</td><td>Moisture Resistance MIL-STD-202, Method 106, No Measurements at High Humidity</td></tr><tr><td>Insertion Loss (dB MAX) .15 V(fGHz)</td><td>Withdrawal (MIN Oz) N/A</td><td>Corrosion - MIL-STD-202, Method 101, Condition B, 5% salt spray</td></tr><tr><td>RF Leakage (dB MIN) -(60-fGHz)</td><td>Force to Engage and Disengage (In-Lbs MAX) 2.0</td><td></td></tr><tr><td>Corona, 70,000 Ft (VRMS MIN) 250</td><td>Center Contact Captivation</td><td></td></tr><tr><td>Dielectric Withstanding Voltage (VRMS MIN) Sea Level 1,000</td><td>Axial (Lbs) 6.0</td><td></td></tr><tr><td>Contact Resistance (Milliohms MAX)</td><td>Radial (In-Oz) 4.0</td><td></td></tr><tr><td>Center Contact 4.0</td><td>Cable Retention</td><td></td></tr><tr><td>Outer Contact 2.0</td><td>Axial Force (Lbs) 40 Min</td><td></td></tr><tr><td>Cable to Housing .05</td><td>Torque (In-Oz) N/A</td><td></td></tr><tr><td>RF High Potential Sea Level (VRMS MIN 5 MHz) 670</td><td>Weight (Grams) TBD</td><td></td></tr><tr><td>I.R.(Megohms MIN) 5,000</td><td></td><td></td></tr></table>		ELECTRICAL	MECHANICAL	ENVIRONMENTAL	Nominal Impedance (Ohms) 50	Interface Dimensions MIL-STD-348A, Fig. 310.1	Temperature Rating -65°C to +165°C	Frequency Range (MHz) DC TO 12,400	Recommended Mating	Vibration MIL-STD-202, Method 204, Condition D	Volt Rating (VRMS MAX)	Torque 7-10 In-Lbs	Shock MIL-STD-202, Method 213, Condition I	Sea Level 335	Mating Characteristics:	Thermal Shock MIL-STD-202, Method 107, Condition B, Except High Temp +85°C	VSWR 1.15+-.02f(GHz)	Insertion (MAX Lbs) N/A	Moisture Resistance MIL-STD-202, Method 106, No Measurements at High Humidity	Insertion Loss (dB MAX) .15 V(fGHz)	Withdrawal (MIN Oz) N/A	Corrosion - MIL-STD-202, Method 101, Condition B, 5% salt spray	RF Leakage (dB MIN) -(60-fGHz)	Force to Engage and Disengage (In-Lbs MAX) 2.0		Corona, 70,000 Ft (VRMS MIN) 250	Center Contact Captivation		Dielectric Withstanding Voltage (VRMS MIN) Sea Level 1,000	Axial (Lbs) 6.0		Contact Resistance (Milliohms MAX)	Radial (In-Oz) 4.0		Center Contact 4.0	Cable Retention		Outer Contact 2.0	Axial Force (Lbs) 40 Min		Cable to Housing .05	Torque (In-Oz) N/A		RF High Potential Sea Level (VRMS MIN 5 MHz) 670	Weight (Grams) TBD		I.R.(Megohms MIN) 5,000			<table><tr><td>COMPONENT</td><td>MATERIAL</td><td>FINISH</td></tr><tr><td>UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCE ON</td><td>DRAWN BY </td><td>DATE 10/2/96</td></tr><tr><td>FRAC DEC ANGLES</td><td>CHECKED BY </td><td>DATE 3/13/97</td></tr><tr><td>+ 1/64 +.005 + 1°</td><td>APP'D BY </td><td>DATE 3/13/97</td></tr><tr><td>These drawings and specifications are the property of M/A-COM Incorporated and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.</td><td>USE ASS'Y PROCEDURE</td><td>408-04846 NO. A.P. (20-584)</td></tr><tr><td colspan="2">TITLE OSM RIGHT ANGLE CABLE PLUG - CRIMP ATTACHMENT M39012/56-3129 CAT C</td><td>SIZE B</td></tr><tr><td colspan="2">CODE IDENT NO. 26805</td><td>2037-8129-92</td></tr><tr><td colspan="2">SCALE 3:1</td><td>REV 010</td></tr><tr><td colspan="2">SHEET 1 OF 1</td><td></td></tr></table>				COMPONENT	MATERIAL	FINISH	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCE ON	DRAWN BY	DATE 10/2/96	FRAC DEC ANGLES	CHECKED BY	DATE 3/13/97	+ 1/64 +.005 + 1°	APP'D BY	DATE 3/13/97	These drawings and specifications are the property of M/A-COM Incorporated and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.	USE ASS'Y PROCEDURE	408-04846 NO. A.P. (20-584)	TITLE OSM RIGHT ANGLE CABLE PLUG - CRIMP ATTACHMENT M39012/56-3129 CAT C		SIZE B	CODE IDENT NO. 26805		2037-8129-92	SCALE 3:1		REV 010	SHEET 1 OF 1		
ELECTRICAL	MECHANICAL	ENVIRONMENTAL																																																																														
Nominal Impedance (Ohms) 50	Interface Dimensions MIL-STD-348A, Fig. 310.1	Temperature Rating -65°C to +165°C																																																																														
Frequency Range (MHz) DC TO 12,400	Recommended Mating	Vibration MIL-STD-202, Method 204, Condition D																																																																														
Volt Rating (VRMS MAX)	Torque 7-10 In-Lbs	Shock MIL-STD-202, Method 213, Condition I																																																																														
Sea Level 335	Mating Characteristics:	Thermal Shock MIL-STD-202, Method 107, Condition B, Except High Temp +85°C																																																																														
VSWR 1.15+-.02f(GHz)	Insertion (MAX Lbs) N/A	Moisture Resistance MIL-STD-202, Method 106, No Measurements at High Humidity																																																																														
Insertion Loss (dB MAX) .15 V(fGHz)	Withdrawal (MIN Oz) N/A	Corrosion - MIL-STD-202, Method 101, Condition B, 5% salt spray																																																																														
RF Leakage (dB MIN) -(60-fGHz)	Force to Engage and Disengage (In-Lbs MAX) 2.0																																																																															
Corona, 70,000 Ft (VRMS MIN) 250	Center Contact Captivation																																																																															
Dielectric Withstanding Voltage (VRMS MIN) Sea Level 1,000	Axial (Lbs) 6.0																																																																															
Contact Resistance (Milliohms MAX)	Radial (In-Oz) 4.0																																																																															
Center Contact 4.0	Cable Retention																																																																															
Outer Contact 2.0	Axial Force (Lbs) 40 Min																																																																															
Cable to Housing .05	Torque (In-Oz) N/A																																																																															
RF High Potential Sea Level (VRMS MIN 5 MHz) 670	Weight (Grams) TBD																																																																															
I.R.(Megohms MIN) 5,000																																																																																
COMPONENT	MATERIAL	FINISH																																																																														
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCE ON	DRAWN BY	DATE 10/2/96																																																																														
FRAC DEC ANGLES	CHECKED BY	DATE 3/13/97																																																																														
+ 1/64 +.005 + 1°	APP'D BY	DATE 3/13/97																																																																														
These drawings and specifications are the property of M/A-COM Incorporated and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.	USE ASS'Y PROCEDURE	408-04846 NO. A.P. (20-584)																																																																														
TITLE OSM RIGHT ANGLE CABLE PLUG - CRIMP ATTACHMENT M39012/56-3129 CAT C		SIZE B																																																																														
CODE IDENT NO. 26805		2037-8129-92																																																																														
SCALE 3:1		REV 010																																																																														
SHEET 1 OF 1																																																																																

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[1052207-1](#)