



## RC/RM Machined contact AWG16

A unique contact technology for a wide range of railway connectors

**Qualified for railway applications** ■ Machined crimp contact

**Low contact resistance** ■ Gold plated

**Good contact retention** ■ Locking spring

**Suitable for automatic crimping** ■ Available on plastic carrier

## Technical features

- Machined crimp contact
- **Contact body:** High conductive copper alloy
- **Plating:** K (Std) Min. 0.4µm gold all over, over nickel
- **Current per contact max.:** 15A according to NFF61030
- **Contact resistance:** ≤ 3 MΩ
- **Contact retention in body:** 110 N min.
- **Individual insertion force:** 3.5 N max.
- **Individual withdrawal force:** 0.55 N min
- RC/RM machined contact size 16 can be used in any contact position UTS, UTO, VGE1 and 838 connectors

## Ordering information

<b>Type</b>	(K)RM	16	M	23	(GE1)	K
RM: Male contact bulk packing	(K)RC	16	M	23	(GE1)	K
RC: Female contact bulk packing						
KRM: Male contact on plastic carrier strip						
KRC: Female contact on plastic carrier strip						
<b>Wire size</b>						
#14 – #16 – #20 – #24 – #28						
<b>Contact size #16</b>						
.0625" (1.6mm) diameter contacts						
Design variation: Crimp barrel						
<b>Contact type</b>						
No digit: Pin						
GE1: Longer contact						
GE3: Shorter contact (only male contact)						
GE7: Shorter contact (only female contact)						
<b>Plating indication:</b>						
K: Gold						
Other plating on request						
<b>Packing quantity</b>						
No digit (std): 50 pcs bulk packing (RM/RC)						
2000 pcs on reel (KRM/KRC)						
1000: 1000 pcs bulk packing (RM/RC)						

## The RM/RC machined contact packing

Conscious of the wide variety of applications, contact packaging has been considered for small series (bulk packaging) and high volume production (reeled contacts):



- 50 pieces bulk package (machined contacts)



- 1000 pieces bulk package (machined contacts)



- 5000 pieces reeled (machined contacts)

## RM/RC machined contacts



**Part numbers & dimensions**

Part numbers				Wire size		Max. wire Ø	Max. insul. Ø	Wire strip length	O.D.**	L1	L2
Male contact	FIG.	Female contact	FIG.	AWG	mm <sup>2</sup>						
RM28M1K	1	RC28M1K	6	30-28	0.05-0.08	0.55	1.1	4.8	1.90	26.2	18.2
RM24M9K	2	RC24M9K	7	26-24	0.13-0.20	0.8	1.6		2.55		
RM20M13K	3	RC20M13K	8	22-20	0.32-0.52	1.18	1.8		2.92		
RM20M12K		RC20M12K					2.2	2.92			
RM16M23K	4	RC16M23K	9	20-16	0.50-1.50	1.80	3.2	7.1	2.55	26.2	18.2
RM14M50K	5	RC14M50K	10	16-14	1.5-2.5	2.05			3.10		
RM14M30K	5	RC14M30K	10	16-14	1.5-2.5	2.28			3.10		

For machined contacts reeled on plastic carrier: put «K» in front of part number example: KRM16M13K

**Dimensions**

**Comparison with standard RM / RC contacts**

	GE1	GE3	GE7
RM contact (male contact)	+ 1 mm	-1 mm	-
RC contact (female contact)	+ 1.5 mm	-	-0.6 mm

**Contact selector guide**

	Standard RC contact	RM*GE1	RC*GE7
Standard RC contact			
Standard RM contact			Last Mate, First Break
RM*GE1	First Mate, Last Break		

First Mate, Last Break contact can be used as grounding contact.

Note : all dimensions are in mm / \*\* Outer diameter

RM/RC machined contact

Longer											
Part numbers				Wire size		Max. wire Ø	Max. insul. Ø	Wire strip length	O.D.**	L1	L2
Male contact	FIG.	Female contact	FIG.	AWG	mm²						
RM28M1GE1K	1	RC28M1GE1K	6	30-28	0.05-0.08	0.55	1.1	4.8	1.90	27.2	19.7
RM24M9GE1K	2	RC24M9GE1K	7	26-24	0.13-0.20	0.8	1.6		2.55		
RM20M13GE1K	3	RC20M13GE1K	8	22-20	0.32-0.52	1.18	1.8		2.92		
RM20M12GE1K		RC20M12GE1K					2.2	2.55			
RM16M23GE1K	4	RC16M23GE1K	9	20-16	0.52-1.50	1.80	3.2	7.1	2.55		
RM14M50GE1K	5	RC14M50GE1K	10	16-14	1.5-2.5	2.05			3.10		
RM14M30GE1K	5	RC14M30GE1K	10			2.28					

Shorter											
Part numbers				Wire size		Max. wire Ø	Max. insul. Ø	Wire strip length	O.D.**	L1	L2
Male contact	FIG.	Female contact	FIG.	AWG	mm²						
RM28M1GE3K	1	RC28M1GE7K	6	30-28	0.05-0.08	0.55	1.1	4.8	1.90	25.2	17.6
RM24M9GE3K	2	RC24M9GE7K	7	26-24	0.13-0.20	0.8	1.6		2.55		
RM20M13GE3K	3	RC20M13GE7K	8	22-20	0.32-0.52	1.18	1.8		2.92		
RM20M12GE3K		RC20M12GE7K					2.2	2.55			
RM16M23GE3K	4	RC16M23GE7K	9	20-16	0.52-1.50	1.80	3.2	7.1	2.55		
RM14M50GE3K	5	RC14M50GE7K	10	16-14	1.5-2.5	2.05			3.10		
RM14M30GE3K	5	RC14M30GE7K	10			2.28					

Crimptooling											
Stripping length	Wire size		Part numbers		Tool	Locator	Tool selector	Extraction tool			
	AWG	mm²									
4.8	30-28	0.05-0.08	RM28M1*	RC28M1*	MH860 (M22520/7-01)	MH86164G	4/6	RX2025GE1			
	26-24	0.13-0.2	RM24M9*	RC24M9*	MH860 (M22520/7-01)	MH86164G	5/6				
	22-20	0.32-0.52	RM20M12*	RC20M12*	MH860 (M22520/7-01)	MH86164G	5/7				
7.1	20-16	0.5-1.5	RM16M23*	RC16M23*	MH860 (M22520/7-01)	MH86164G	6/8				
	16-14	1.5-2.5	RM14M30	RC16M30*	AF8 (M22520/1-01)	TP1142	8				
	16-14	1.5-2.5	RM14M50*	RC14M50*	AF8 (M22520/1-01)	TP1142	8				

**SOURIAU**  
 railway-connectors.com

contactindustry@souriau.com

**SOURIAU**

Note : all dimensions are in mm

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

## Souriau:

[851-07A84P5044A7](#) [851-07A1419SW5044A7](#) [851-07A84SW5044A7](#) [851-06A168PW2966](#) [851-06A1811P2966](#)  
[851-06A168P2966](#) [851-07A2221P50A7](#) [851-07B1210S54A7](#) [851-07A2039P5066](#) [851-02A2016S50](#) [851-02A1626S5029](#) [851-01RM1626P50](#) [851-06EC1412SX5466](#) [851-06J2461S50](#) [851-00A2461S50](#) [3330102](#) [3330103](#)  
[3330110](#) [3330108](#) [3330104](#) [3330109](#) [3330107](#) [3330106](#) [3330105](#) [851-07B128PX54A7](#) [851-06E2039P2966](#) [851-06E2039S2966](#) [851-06A2024P5066](#) [851-06A2221S50](#) [851-01A1419P5066](#) [851-01A2221S5066](#) [851-01EC2041P50](#)  
[851-00EC2236P50](#) [851-00AC1415P50](#) [851-00AC145S50](#) [851-00AC1623S50](#) [851-00AC1811P50](#) [851-00AC1832S50](#)  
[851-00AC2016P50](#) [851-00AC2016S50](#) [851-00AC2039P50](#) [851-00AC2041P50](#) [851-00AC2041S50](#) [851-00AC2255P50](#) [851-00E1623P50](#) [851-00E1623S50](#) [851-00E1811P50](#) [851-00E1811S50](#) [851-00E2221P50](#) [851-00E2221PW50](#) [851-00EC1418P50](#) [851-00EC1418SX50](#) [851-00EC1626P50](#) [851-00EC1626PY50](#) [851-00EC168S50](#)  
[851-00EC2016S50](#) [851-00EC2461PX50](#) [851-00EC2461PY50](#) [851-00P1415PY50](#) [851-01AC1623P50](#) [851-01AC1623S50](#) [851-01AC1626S50](#) [851-01AC168S50](#) [851-01AC1832S50](#) [851-01AC2016S50](#) [851-01AC2039S50](#)  
[851-01AC2221P50](#) [851-01AC2255S50](#) [851-01AC2461P50](#) [851-01E1418PY50](#) [851-01E1623P50](#) [851-01E1623S50](#)  
[851-01E2039SY50](#) [851-01E2041S50](#) [851-01E2255P50](#) [851-01E2255S50](#) [851-01EC1412P50](#) [851-01EC1623P50](#)  
[851-01EC1626PW50](#) [851-01EC1811S50](#) [851-01EC1832S50](#) [851-01EC2255P50](#) [851-01EC2255S50](#) [851-01P106PW50](#) [851-01P106SW50](#) [851-01RC1626PZ50](#) [851-01T2255P50](#) [851-02E2041PY50](#) [851-02E2221SZ50](#)  
[851-06AC2039P50](#) [851-06E1418PX50](#) [851-06E1418SX50](#) [851-06E1811P50](#) [851-06E1832P50](#) [851-06E2221P50](#)  
[851-06E2255PX50](#) [851-06E2255SX50](#) [851-06E2255SZ50](#) [851-06EC1626PY50](#) [851-06J2255S50](#)