

## Monitor - VL FPM 15 - 2913017

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



15"/38.1 cm flat panel LCD monitor with resistive touch screen. Includes two rear USB ports.

15-in. display shown



### Key Commercial Data

Packing unit	1 pc
Custom tariff number	85299020
Country of origin	Taiwan

### Technical data

#### Dimensions

Installation dimension, width	386.6 mm
Installation dimension, height	285 mm
Note regarding installation dimension	Panel cutout

#### Display

Display	38.1 cm/15" TFT
Screen resolution	1024 x 768 Pixel(s) (XGA)
Backlighting	CCFL
Display backlight MTBF	> 50000 h
Touch technology	Analog resistive
Colors	16.2 million colors

#### Monitor data

Network	Without network
Interfaces	1x USB 1.1, Typ A 1x USB 2.0, Typ A
Monitor output	1x DVI-D

# Monitor - VL FPM 15 - 2913017

## Technical data

### Monitor data

	1x VGA
Slots	without slots

### General

Mounting type	VESA MIS-D, 100/75, C
	Front installation
Weight	4.51 kg

### Ambient conditions

Degree of protection	IP65 (front), IP20 (back)
Ambient temperature (operation)	0 °C ... 55 °C
Ambient temperature (storage/transport)	-40 °C ... 70 °C
Permissible humidity (operation)	5 % ... 95 %
Permissible humidity (storage/transport)	5 % ... 95 %
Vibration (operation)	DIN EN 60068-2-6
Shock	15g, 11 ms in accordance with IEC 60068-2-27

### Device supply

Supply voltage	24 V DC (typical)
Supply voltage range	19.2 V DC ... 28.8 V DC
Power supply unit	24 V DC ±20 %

### Standards and Regulations

Shock	15g, 11 ms in accordance with IEC 60068-2-27
Vibration (operation)	DIN EN 60068-2-6

## Classifications

### eCl@ss

eCl@ss 5.1	27242402
eCl@ss 6.0	19200201
eCl@ss 8.0	19200403

### ETIM

ETIM 3.0	EC001425
ETIM 4.0	EC001428
ETIM 5.0	EC001428

### UNSPSC

UNSPSC 12.01	43211902
--------------	----------

## Monitor - VL FPM 15 - 2913017

### Accessories

#### Spare parts

Printed-circuit board connector - MSTB 2,5/ 3-STF - 1786844

Plug component, Nominal current: 12 A, Rated voltage (III/2): 320 V, Number of positions: 3, Pitch: 5 mm, Connection method: Screw connection with tension sleeve, Color: green, Contact surface: Tin



# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Phoenix Contact:](#)

[2913017](#)