

PART NUMBER	LENGTH		ITEM ① UMC RIGHT ANGLE PLUG CONNECTOR, LOW PROFILE	ITEM ② CABLE
	INCH	mm		
415-0084-050	1.97±.16	50±4	BODY - COPPER ALLOY- GOLD PLATED	SHIELD - TIN PLATED ANNEALED COPPER WIRE
415-0084-100	3.94±.16	100±4	CONTACT - COPPER ALLOY - GOLD PLATED	DIELECTRIC - FEP
415-0084-150	5.91±.16	150±4	INSULATOR - LCP - WHITE, UL94V-0	CENTER CONDUCTOR - SILVER PLATED ANNEALED COPPER WIRE, AWG#36 (7/.002)
415-0084-200	7.87±.16	200±4		JACKET - FEP -GREY WHITE
415-0084-250	9.84±.31	250±8		
415-0084-300	11.81±.31	300±8		
415-0084-500	19.69±.31	500±8		

DRAWING NO.
B - 415-0084-001/999

0 REVISIONS

ENGINEERING RELEASE


1	10-20-06	PAT	SDB	RJB	PDW	12-20-06	ECN 50727
---	----------	-----	-----	-----	-----	----------	-----------

INSULATOR-LCP BLACK WAS WHITE

 * REVISION NUMBER FOLLOWED BY AN ALPHA *
 * CHARACTER INDICATES DRAWING CLARIFI- *
 * CATION OR PART NUMBER ADDITION ONLY. *

1a	2-20-07	PAT	SDB	RJB	MJUN	4-23-07	ECN 50949
----	---------	-----	-----	-----	------	---------	-----------

1b	2-7-11	MS	SDB	RJB	MS	2-7-11	ECO 52911
----	--------	----	-----	-----	----	--------	-----------



NOTES:

1. SPECIFICATIONS:

IMPEDANCE: 50 OHMS
 FREQUENCY RANGE: 0-6 GHz
 VSWR: 1.30 MAX AT 0-3 GHz
 1.50 MAX AT 3-6 GHz
 WITHSTANDING VOLTAGE: 200 V AC
 INSULATION RESISTANCE: 500 MEGOHM MIN
 CONTACT RESISTANCE:
 CENTER CONTACT - 20 MILLI-OHMS MAX
 OUTER CONDUCTOR - 20 MILLI-OHMS MAX

MECHANICAL:

COMPATIBILITY: MATES WITH U.FL SERIES
 HOLDING FORCE (MIN): 0.15 N (FEMALE CONTACT)
 DURABILITY: 30 CYCLES

ENVIRONMENTAL:

TEMPERATURE RANGE: -40°C TO +90°C

CUSTOMER DRAWING

THIS DRAWING TO BE INTERPRETED
 PER ASME Y 14.5M - 1994

"μ STATION"

COMPANY CONFIDENTIAL

TOLERANCE UNLESS OTHERWISE SPECIFIED	DRAWN BY PAT	DATE 5-23-06
DECIMALS .XX _____	CHECKED BY RJB	DATE 12-13-06
mm _____	APPROVED BY PDW	DATE 12-20-06
.XXX ±.004 _____	RELEASE DATE 12-20-06	
MATL _____	U/M INCH	SCALE 10:1
FINISH _____		

cinch
CONNECTIVITY SOLUTIONS
a bel group

Cinch Connectivity Solutions
P.O. Box 1732
Waseca, MN 56093
1-800-247-8256

TITLE
UMC MATING CABLE PLUG
.079 (2.0mm) MATING HEIGHT
.032 (0.81mm) CABLE O.D.

SHEET
2 OF 2

DRAWING NO.
B - 415-0084-001/999

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Cinch Connectivity Solutions:](#)

[415-0084-300](#)