

SAFETY ORGANIZATION(S).

THIS FILTER HAS BEEN FORMALLY RECOGNIZED, CERTIFIED OR APPROVED BY THE LISTED AGENCY. THEREFORE, ALL TEST/REQUIREMENTS SPECIFIED IN THE LATEST REVISION OF THE FOLLOWING AGENCY STANDARDS HAVE BEEN MET.

UL 1283
 CSA 22.2 NO. 0, 0.4, 8
 VDE 0565-3 (20AYT6C ONLY)

OPERATING SPECIFICATIONS.

LINE VOLTAGE/CURRENT:
 20 OR 30 AMP., 250VAC PHASE/NEUTRAL-GND
 20 OR 30 AMP., 440VAC PHASE/PHASE
 50-60Hz
 LINE FREQUENCY,
 40°C
 MAX. CASE RISE θ RATED CURRENT,
 1.4mA @ 120V 60Hz
 MAX. LEAKAGE CURRENT, EACH
 3.4mA @ 250V 50Hz
 LINE TO GROUND
 OPERATING AMBIENT TEMP. RANGE,
 -10°C TO +40°C @ RATED CURRENT, I_r

IN AN AMBIENT, T_a , HIGHER THAN 40°C, THE MAXIMUM OPERATING CURRENT, I_o , IS AS FOLLOWS,

$$I_o = I_r \sqrt{\frac{85 - T_a}{45}}$$

RELIABILITY SPECIFICATIONS.

STORAGE TEMPERATURE,
 -25°C TO +85°C
 HUMIDITY,
 21 DAYS @ 40°C 95% RH

TEST SPECIFICATIONS.

INDUCTANCE,
 20A = 7.0mH NOMINAL
 30A = 3.32mH NOMINAL
 GROUND CHOKE, .261mH NOMINAL
 CAPACITANCE, (MEASURED @ 1 KHz, 0.25 VAC MAX., 25°C $\pm$ 1°C)
 PHASE/NEUTRAL TO GROUND,
 .026 μ F $\pm$ 20%
 PHASE TO NEUTRAL,
 4.47 μ F $\pm$ 20%
 DISCHARGE RESISTOR,
 73.3K OHMS
 INSULATION RESISTANCE
 6000 M Ω (MIN) AT 100 VDC
 LINE/GROUND AND LINE/LINE
 20°C AND 50% RH
 (W/O DISCHARGE RESISTOR)
RECOMMENDED RECEIVING INSPECTION HIPOIT.
 PHASE/NEUTRAL TO GROUND,
 1500 VAC FOR 1 MINUTE
 PHASE TO NEUTRAL,
 1450 VDC FOR 1 MINUTE


FILTER APPROVAL.

THE BEST WAY TO SELECT AND QUALIFY A FILTER IS FOR YOUR ENGINEERING TO TEST THE UNIT IN YOUR EQUIPMENT.



POWER LINE FILTER

SCALE	NTS	DATE	4-25-89	DRG. NO.	20AYT6C & 30AYT6C	REV.	4
BY	LJD	ORIGINATOR	CFW				




- NOTES:
 1.) UNLESS OTHERWISE SPECIFIED, TOLERANCE TO BE $\pm$.030
 2.) LINE SIDE HAS INSULATED GROUND TERMINAL.

NOTE: COMMON MODE A-B-C & N SHORTED TOGETHER.
 DIFF. MODE MEASURED N TO A-B-C SHORTED TOGETHER.

50 Ω - 50 Ω (MINIMUM) INSERTION LOSS									
FREQUENCY MHz	.05	.15	.5	1.0	5.0	10.0	30.0		
COMMON 20A	45	70	75	75	75	75	65		
30A	29	61	75	75	75	75	70		
DIFF. 20A	27	65	70	70	70	70	70		
30A	17	55	75	75	75	75	70		

This document is proprietary to CORCOM INC. and is not to be reproduced nor used for manufacturing purposes except on CORCOM's order or prior written consent.



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[20AYT6C](#) [6609073-1](#)