



- 注記:
1. 製品規格 : 108-5437
 2. 取付適用規格 : 114-5195
 3. 適用ハウジング : 179970-□
1318954-□
 4. 取扱説明書 : 411-5691

- NOTE:
1. PRODUCT SPEC : 108-5437
 2. APPLICATION SPEC : 114-5195
 3. APPLICABLE HOUSING P/N : 179970-□
1318954-□
 4. INSTRUCTION SHEET : 411-5691

— 11 —	錫めっき済高耐熱銅合金 (PRE TINNED HIGH HEAT RESISTANCE COPPER ALLOY)	179974-6
179989-1	錫めっき済黄銅 (PRE TINNED BRASS)	179974-1
プラグ端子型番 (L/P No.)	材料 (MATERIAL)	型番 (P/N)



一般公差 (GENERAL TOLERANCE)	包含電線断面積 (WIRE RANGE) 0.76 2.09 mm ² (AWG#18-#14)	絶縁外径 (INSULATION DIA.) 2.2-3.4 mm
10以下 : ±0.2 10以上 30以下 : ±0.25 30以上 100以下 : ±0.3 角 度 : ±3°	材料 (MATERIAL) 表参照 (SEE TABLE)	仕上 (FINISH) — 11 —

PRINT DISI	C1	REVISED PER ECO-11-005294	RK	HMR	06APR 11	尺度 (SCALE)	LOC	番号 (No.)	REV.	SHEET
	LTR	変更 (REVISION RECORD)	DR	CHK	DATE	4-1	A	J	C1	1 OF 1
	DR.	30 JUN '94 N. NAGASHIMA	DE.	4 JUL '94 M. SUZUKI	名称 (NAME)	"250" SERIES POSITIVE LOCK-EX-II REC. "250" シリーズ・ポジティブロック-EX-II) セブタクル				
CHK.	4 JUL '94 M. SHINDO	APP.	4 JUL '94 Y. KASHIWA							

CUSTOMER DRAWING

単位: 寸法 DIMENSIONS IN MM. DO NOT SCALE PRINT

NUMBER 179974

三 角 法 (3rd ANGLE PROJECTION)

METRIC

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[179974-1 \(Mouser Reel\)](#) [179974-1 \(Cut Strip\)](#)