

Interface module - VIP-2/PT/FLK16/LED - 2904250

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



VARIOFACE module, with push-in connection and flat-ribbon cable connector, for mounting on NS 35 rails, with pin strip and short and long locking latches for socket strips, 16-pos., with LED

The illustration shows a 14-position version



Key Commercial Data

Packing unit	1 pc
Weight per Piece (excluding packing)	121.5 g
Custom tariff number	85369010
Country of origin	United States

Technical data

Dimensions

Width	46.9 mm
Height	72.1 mm
Depth	56 mm

Ambient conditions

Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C

General

Max. perm. operating voltage	24 V DC
Max. perm. current (per branch)	1 A
Number of positions	16
Status display	LED
Mounting position	any
Standards/regulations	IEC 60664
	DIN EN 50178

Interface module - VIP-2/PT/FLK16/LED - 2904250

Technical data

General

	IEC 62103
Degree of pollution	2
Overvoltage category	II

Connection data for connection 1

Connection name	Field level
Connection method	Push-in connection
Stripping length	8 mm
Conductor cross section solid	0.14 mm ² ... 2.5 mm ²
Conductor cross section flexible	0.14 mm ² ... 2.5 mm ²
Conductor cross section AWG	26 ... 14

Connection data for connection 2

Connection name	Controller level
Connection method	IDC/FLK pin strip (2.54 mm)
Number of connections	1
Number of positions	16
Pitch	2.54 mm

Standards and Regulations

Connection in acc. with standard	CSA
Standards/regulations	IEC 60664
	DIN EN 50178
	IEC 62103
Degree of pollution	2
Overvoltage category	II

Classifications

eCl@ss

eCl@ss 4.0	27250313
eCl@ss 4.1	27250313
eCl@ss 5.0	27250313
eCl@ss 5.1	27250313
eCl@ss 6.0	27242608
eCl@ss 7.0	27141152
eCl@ss 8.0	27141152
eCl@ss 9.0	27141152

Interface module - VIP-2/PT/FLK16/LED - 2904250

Classifications

ETIM

ETIM 3.0	EC001604
ETIM 4.0	EC001604
ETIM 5.0	EC002780

UNSPSC

UNSPSC 6.01	30211824
UNSPSC 7.0901	39121421
UNSPSC 11	39121421
UNSPSC 12.01	39121421
UNSPSC 13.2	39121421

Approvals

Approvals

Approvals

CSA / UL Recognized / cUL Recognized / EAC / EAC / cULus Recognized

Ex Approvals

Approvals submitted

Approval details

CSA 	
mm ² /AWG/kcmil	26-14
Nominal current I _N	1 A
Nominal voltage U _N	24 V

Interface module - VIP-2/PT/FLK16/LED - 2904250

Approvals

UL Recognized 	
mm²/AWG/kcmil	26-14
Nominal current I _N	1 A
Nominal voltage U _N	24 V

cUL Recognized 	
mm²/AWG/kcmil	26-14
Nominal current I _N	1 A
Nominal voltage U _N	24 V

EAC

EAC

cULus Recognized 
--

Accessories

Accessories

System cable

Cable - FLK 16/EZ-DR/ 50/KONFEK - 2299291



Round cable set, with two 16-pos. socket strips (1:1 connection), cable length: 0.5 m

Interface module - VIP-2/PT/FLK16/LED - 2904250

Accessories

Cable - FLK 16/EZ-DR/ 100/KONFEK - 2299301



Round cable set, with two 16-pos. socket strips (1:1 connection), cable length: 1 m

Cable - FLK 16/EZ-DR/ 150/KONFEK - 2299314



Round cable set, with two 16-pos. socket strips (1:1 connection), cable length: 1.5 m

Cable - FLK 16/EZ-DR/ 200/KONFEK - 2299327



Round cable set, with two 16-pos. socket strips (1:1 connection), cable length: 2 m

Cable - FLK 16/EZ-DR/ 300/KONFEK - 2299330



Round cable set, with two 16-pos. socket strips (1:1 connection), cable length: 3 m

Cable - FLK 16/EZ-DR/ 400/KONFEK - 2299343



Round cable set, with two 16-pos. socket strips (1:1 connection), cable length: 4 m

Interface module - VIP-2/PT/FLK16/LED - 2904250

Accessories

Cable - FLK 16/EZ-DR/ 800/KONFEK - 2299369



Round cable set, with two 16-pos. socket strips (1:1 connection), cable length: 8 m

Cable - FLK 16/EZ-DR/1000/KONFEK - 2299372



Round cable set, with two 16-pos. socket strips (1:1 connection), cable length: 10 m


Cable - FLK EZ-DR.../.../... - 2295059



Round cable, with preassembly, not shielded, variable cable length

Drawings

Circuit diagram



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Phoenix Contact:](#)

[2904250](#)