

Blind rivet - RVT-AL/ST 4/12 - 3240516

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Blind rivets, Ø 4.0 mm, 12 mm sleeve length, aluminum sleeve, zinc-plated steel pin, flat head, standard version similar to DIN 7337 A

Why buy this product

- ✓ Special rivets are available for fixing RW... and UW... high-current panel feed-through terminal blocks that are specifically designed for terminal blocks
- ✓ Compact, ergonomically shaped pliers
- ✓ 3 inserts for rivet diameter of 2.4 - 3.2 mm, 4 mm, and 4.8 - 5.0 mm

Key Commercial Data

Packing unit	500 pc
GTIN	 4 046356 527477
GTIN	4046356527477

Technical data

Dimensions

Length (b)	12 mm
Hole diameter	4.1 mm
Diameter	4 mm
Max. material thickness	8.5 mm
Material thickness (g)	6.5 mm

General

Color	silver
Material	Aluminum (AlMg 3/3.5)/galvanized steel

Phoenix Contact 2018 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Phoenix Contact:](#)

[3240516](#)