


VOLEX RESERVES THE RIGHT TO ALTER NON-CRITICAL DIMENSIONS WITHOUT NOTICE.

**NOTES**

- 1) 23 AWG, 4 CONDUCTOR WITH 21 STRANDS OF 36AWG TINNED COPPER.
- 2) CONDUCTORS: RUBBER INSULATED
- 3) CONDUCTOR COLOR CODE: BLACK, WHITE, GREEN, AND RED.
- 4) JACKET INSULATION TO BE NEOPRENE.
- 5) CORDAGE D.D.: .250" NDM.
- 6) APPROVALS: NONE
- 7) RATING: 60°C / 300 VOLTS MAX.
- 8) PACKAGING: 25 CORDS/CARTON
- 9) ALL DIMENSIONS IN INCHES UNLESS OTHERWISE SPECIFIED.



**CUD**

FORM IN71-07 REV.A

- Indianapolis, IN
- Conover, N.C.
- Freemont, CA
- Aguascalientes, MX
- Tijuana, Mexico
- Hermosillo, MX
- Clinton, AR
- Kanata, Canada

**Proprietary Notice:**

This document is the property of Volex Incorporated. The information contained herein is not to be disclosed to anyone without the express written consent of Volex Inc.

MUST BE ROHS COMPLIANT

FINISH: JACKET: SMOOTH

REV	SCALE:	NDT TO SCALE	ECD:	ITEM DESCRIPTION	DATE
1			N/A	C.U.D - NEW RELEASE	9/6/07

APPROVED	DRAWN BY	DATE:
STC	STC	9/6/07

RETRACTILE CORD - NORTH AMERICAN	PART NO.
	6415

TOLERANCE UNLESS OTHERWISE SPECIFIED  
 .XXX ± .005  
 .XX ± .02  
 .X ± .03  
 FRACT. ± 1/32°  
 ANGULAR ± 1/2°

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Volex:](#)

[6415](#)