SCT Splice Cover (Dual Wall) Heat-Shrinkable Tubing




Table 1: <u>Dimensions</u> mm(inches)

RELEASED FOR PUBLICATION

TE Connectivity

2017

COPYRIGHT

lol

HIS DRAWING IS UNPUBLISHED.

	As Supplied	As Recovered						
Size	Minimum Expanded I.D. (D)	Maximum Recovered I.D. (d)	Recovered Total Wall (W)	Minimum Recovered Adhesive Wall (W1)				
No. 0	5.10 (0.200)	1.30 (0.050)	1.40 (0.055) ± 0.30 (0.012)	0.76 (0.030)				
No. 1	7.62 (0.300)	1.65 (0.065)	1.52 (0.060) ± 0.30 (0.012)	0.76 (0.030)				
No. 2	9.02 (0.355)	2.29 (0.090)	1.52 (0.060) ± 0.30 (0.012)	0.76 (0.030)				
No. 3	11.56 (0.455)	2.54 (0.100)	2.29 (0.090) ± 0.30 (0.012)	1.40 (0.055)				
No. 3A	14.10 (0.555)	3.00 (0.118)	2.24 (0.088) ± 0.30 (0.012)	1.40 (0.055)				
No. 4	17.78 (0.700)	4.45 (0.175)	2.54 (0.100) ± 0.30 (0.012)	1.52 (0.060)				
No. 5	27.94 (1.100)	8.38 (0.330)	2.54 (0.100) ± 0.30 (0.012)	1.52 (0.060)				
No. 7	33.02 (1.300)	12.70 (0.500)	1.91 (0.075) ± 0.20 (0.008)	0.92 (0.036)				

Color: Jacket shall be black; adhesive liner shall be amber. Marking is SCT-0, SCT-1, SCT-2, SCT-3, SCT-4, SCT-5 and SCT-7. Size SCT-3A is not printed.

Reference Specification TEC-108-120012

-	$ \cdot $										
DIMENSIONS: mm TOLERANCES UNLESS OTHERWISE SPECIFIED:		DIMENSIONS:	DWN J. Bitter	01-JUN-17							
		mm	CHK T. Licko	27-JUN-17				7 .	TE Connoc	stivity	
			APVD T. Licko	27-JUN-17		TE Connectivity 305 Constitution Driv Menlo Park, CA 9402					
0 F		± -	PRODUCT SPEC		NAME	<u> </u>	omectivity	SCT			
2 F	1 PLC		_		Splice Cover Dual Wall						
			APPLICATION SPEC	Heat-Shrinkable Tubing							
4 F	GLES	± - ± -	_		SIZE	CAGE CODE	DRAWING NO				RESTRICTED TO
,		<u>—</u>	WEIGHT O		A4	06090		SCT			_
		$\Psi \Box$	CUSTOMER DE	RAWING				scale None	SHEET 1	OF	1 REV L
1469	1469-35 (1/15)								•		

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

TE Connectivity: SCT-NO.2-E5-0-27MM