

Specification Sheet

Part Number: 170-03036



Braided Sleeving, Expandable, Fray Resistant, Flame Retardant, 0.25" Dia, PET, BK,100 ft/reel

Article Number	170-03036
Type	BSSCFR140
Color	Black (BK)
Features & Benefits	• Provides fuller coverage and a medium-to-high abrasion resistance. • Expands for ease of installation in either the shop or the field. • Increased braid density coverage provides higher level of abrasion resistance without losing flexibility. • Contains white tracer thread for simple identification of flame retardancy. • Treated yarns extinguish quickly and reduces potential flame spread to surrounding components. • Cuts with ordinary scissors without fraying ends.
Quantity Per	reel

Product Description	This protective sleeving is self-extinguishing and can be cut with sharp scissors instead of a hot knife for fray-resistant ends. Readily used in the automotive, audiovisual, industrial, wire, cable and computer industries where flame retardancy is required to reduce the likelihood of ignition and/or reduce the rate of flame spread. It is suited for situations where access to a hot knife is either impractical or impossible.
Short Description	Braided Sleeving, Expandable, Fray Resistant, Flame Retardant, 0.25" Dia, PET, BK,100 ft/reel
Global Part Name	BSSCFR140-PET-BK
Length L (Imperial)	100.0
Length L (Metric)	30.48
Bundle Diameter Min (Imperial)	0.156
Bundle Diameter Min (Metric)	4.0
Bundle Diameter Max (Imperial)	0.437
Bundle Diameter Max (Metric)	11.1
Diameter D (Imperial)	0.25
Diameter D (Metric)	6.4
Nominal Diameter (Imperial)	0.25
Nominal Diameter (Metric)	6.4

Material	Polyester (PET)
Material Shortcut	PET
Flammability	UL VW-1 Mil-202
Halogen Free	Yes
Operating Temperature	-94°F to +257°F (-70°C to +125°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
UL Recognized (US)	Yes
Package Quantity (Imperial)	100
Package Quantity (Metric)	30.48
Customs Number	5808100000
Weight (Metric)	0.18
Weight (Imperial)	0.4

