



Notes:

1. Material and Finish:
 - Receptacle Housing: Polyester (Black); UL94 V-0
 - Panel Nut: Brass, Finish: Nickel Plated
 - Panel Gasket: Silicone, Color: White
 - Duplex LC Adaptor Assembly:
 - Housing: Mod. PPO, UL94 V-0, Color: **SM Blue/MM Beige/APC SM Green** (b)
 - Alignment Sleeves: SM Ceramic/MM Phosphor Bronze
 - Dust Cap: PP, Color: Neutral transparent
 - Operating Temperature: -40~C to +85~C
2. Connector can be front or rear mounted to a maximum panel thickness of 3.2mm.
3. IP67 rated when covered or fully mated with the appropriate mating connector
- (d) 4. Recommended Mounting Panel Nut torque is 20 to 25 lb-inch

Description	Part Number
Single Mode (SM)	17-300010
Multi Mode (MM)	17-300020
(c) APC Single Mode (APC SM)	17-300170

Directive 2002/95/EC RoHS Compliant

Customer:			Tolerance Unless otherwise specified		Autodesk Inventor	Scale: 1.5:1	Dim. in mm
			0 PLC ±0.50	1 PLC ±0.38			
Name			2 PLC ±0.25		Title: IP67 Industrial Duplex LC Receptacle Assembly Kit Plastic Version	Material: See Notes	DIN A3
			3 PLC ±0.10				
Approval Date			ANGLES ±3		Title: IP67 Industrial Duplex LC Receptacle Assembly Kit Plastic Version	Drawing No.: 17K1A002	Sheet 1/1
			Rev. Changes				
d	3 x d	Sep/25/2013	Vincent Ke	Norm	Part No.: SEE PART NUMBER TABLE	DIN A3	Sheet 1/1
c	3 x c	Feb/25/2011	Vincent ke	D-old			
b	1 x b	May/28/2009	Vincent Ke				
a	original						

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[CONEC:](#)

[17-300010](#) [17-300020](#)