

SPECIFICATION

- Part No. : **AA.107.301111**
- Product Name : Stingray Low Profile Adhesive Mount GPS-GLONASS-GALILEO Antenna
- Feature : 1575.42/1602MHz 55mm*51.7mm*10.8mm 3.3V 3M RG174 SMA(M) IP65 Rated Custom cables and connectors available RoHS Compliant





1. Introduction

The Stingray low profile Adhesive Mount (only 10.8mm in height) GNSS antenna is designed for applications which require high positioning accuracy by combining signals from GPS, GLONASS and GALILEO systems. A high gain wide-band patch antenna on an integral ground delivers reliable performance, ideal for those applications that require durability, small size and covert installation, and reliable reception and transmission crossing through different mobile networks.

Its high quality low profile covert housing can be attached onto the glass or even out of sight under the dashboard.

The standard version has 3 metres RG174 cable and SMA(M) connector. The cables and connectors are completely customizable according to customer request.

ELECTRICAL						
Centre Frequency	GPS/GALILEO: 1574.42MHz±3MHz GLONASS: 1602MHz±0.5MHz					
LNA Gain at 3.3V	28dB Typ.					
VSWR	2.0:1					
Impedance	50Ω					
Return Loss	10dB Min.					
Impedance	50Ω					
DC power Input	3.3V					
Noise Figure	2.2dB Typ.					
Power Consumption	10mA Typ.					
MECHANICAL						
Antenna Dimensions	55 x 51.7 x 10.8mm					
Housing Material	UV Resistant ABS					
Cable	3M RG174 (fully customizable)					
Connector	Connector SMA(M) (fully customizable)					
ENVIRONMENTAL						
Operation Temperature	-40°C to 85°C					
Storage Temperature	-40°C to 85°C					
Relative Humidity	40% to 95%					

2. Specification



3. GPS/GLONASS/GALILEO Antenna

3.1. Antenna Block Diagram



3.2. Test Setup





3.4. **VSWR**







3.5. Return loss



3.6. Antenna Radiation Patterns

1575MHz



1602MHz

XZ Plane







3.7. GPS/GLONASS/GALILEO Antenna Gain Chart

Frequency (MHz)	Peak Gain (dBi)	Efficiency (%)
1575	1.36	50.13
1602	0.09	52.64

3.8. GPS/GLONASS/GALILEO LNA Gain



3.9. GPS/GLONASS/GALILEO LNA Output Return Loss





4. Drawing







	Nome	P/N	Materia	Finish	QTY			
1	Housing	000112J000015A	PC	Block	1			
2	Round Label	001011010015A	Art Paper	White	1			
3	Scotch Brand Acrylic Foam Tape	0010111020015A	3M 4612	White Liner	1			
4	Heat Shrink Tube	001315C020000A	PE	Block	1			
5	GPS Label	001011F000015A	PEPA	Orange	1			
	Name	P/N	SPEC	Finish	QTY			
ΥY	Connector Type	200214E000015A	RP-SMA(M)ST	Au Plated	1			
<u>77</u>	Cable Type	301315C00000A	RG174	Black	1			



5. Packaging



Taoglas makes no warranties based on the accuracy or completeness of the contents of this document and reserves the right to make changes to specifications and product descriptions at any time without notice. Taoglas reserves all rights to this document and the information contained herein.

Reproduction, use or disclosure to third parties without express permission is strictly prohibited.

Copyright © Taoglas Ltd.7

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Taoglas: AA.107.301111