


REV. 0  
DCO 143824

COIL: @ 25°C	
RESISTANCE	220 OHMS ±10%
NOMINAL VOLTAGE	9.0 VDC
MUST OPERATE	6.3 VDC
MUST RELEASE	4.2 VDC MAX. 0.9 VDC MIN.

ENVIRONMENT:	
VIBRATION	10 Hz TO 3000 Hz @ 30 g's
SHOCK	75 g's 6 MS. DURATION
TEMPERATURE	-65 °C TO +125 °C
NOTES:-	OPERATE TIME 2.0 MS MAX.
	RELEASE TIME 4.0 MS MAX.
	CONTACT STABILIZATION 2.0 MS MAX.

CUSTOMER DATA SHEET



TERMINAL VIEW

CONTACT RATING: LOW LEVEL TO 1A  
28 VDC RESISTIVE 100,000 OPERATIONS

DR. B.D. 310CT03

*Handwritten signature and date: 10/31/03*

**CII Technologies**  
advanced control electronic solutions

CUST. QPL  
CUST. NO. M39016/20-051P REV.

"JMADD" RELAY

JMACDD-9XP

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[JMACDD-9XP](#)