# ZB5AV6

# light block with body/fixing collar for BA9s bulb <=250V

Product availability: Stock - Normally stocked in distribution facility



#### Main

Commercial Status	Commercialised
Range of product	Harmony XB5
Product or component type	Complete body/light block assembly
Device short name	ZB5
Fixing collar material	Plastic
Sale per indivisible quantity	1
Connections - terminals	Screw clamp terminals: >= 1 x 0.22 mm² without cable end conforming to EN 60947-1 Screw clamp terminals: <= 2 x 1.5 mm² with cable end conforming to EN 60947-1
Light source	Bulb not included
Bulb base	BA 9s
Light block supply	Direct / <= 2.4 W

#### Complementary

[Us] rated supply voltage	<= 250 V	
Signalling type	Steady	
[Uimp] rated impulse withstand voltage	6 kV conforming to EN 60947-1	
[Ui] rated insulation voltage	600 V (degree of pollution: 3) conforming to EN 60947-1	
Shape of screw head	Slotted head compatible with flat Ø 5.5 mm screwdriver Slotted head compatible with flat Ø 4 mm screwdriver Cross head compatible with pozidriv No 1 screwdriver Cross head compatible with Philips no 1 screwdriver	
Tightening torque	7.0810.62 lbf.in (0.81.2 N.m) conforming to EN 60947-1	
Product weight	0.05 lb(US) (0.022 kg)	
Terminals description ISO n°1	(X1-X2)PL	
CAD overall depth	1.26 in (32 mm)	
CAD overall height	1.65 in (42 mm)	
CAD overall width	1.18 in (30 mm)	

#### Environment

D	T-1
Protective treatment	TH
Ambient air temperature for storage	-40158 °F (-4070 °C)
Ambient air temperature for operation	-13158 °F (-2570 °C)
Class of protection against electric shock	Class II conforming to IEC 60536
Standards	EN/IEC 60947-1
	EN/IEC 60947-5-1
	EN/IEC 60947-5-4
	JIS C 4520
	UL 508
	CSA C22.2 No 14
Product certifications	BV
	CSA
	DNV
	GL
	LROS (Lloyds register of shipping)
	RINA
	UL listed
Vibration resistance	5 gn (f = 2500 Hz) conforming to IEC 60068-2-6
Shock resistance	50 gn for 11 ms half sine wave acceleration conforming to IEC 60068-2-27
	30 gn for 18 ms half sine wave acceleration conforming to IEC 60068-2-27

## Ordering and shipping details

Category	22469 - PUSHBUTTON,22MM ACCESSORIES-NEW
Discount Schedule	CS2
GTIN	00785901908289
Nbr. of units in pkg.	1
Package weight(Lbs)	0.06
Product availability	Stock - Normally stocked in distribution facility
Returnability	Υ
Country of origin	FR

### Contractual warranty

Dariad	10 months
Period	16 MONUS



# **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Schneider Electric: ZB5AV6