Ultra-R2 Dissipative Rubber Table Mat

Meets ANSI/ESD S20.20 worksurface required limit (and recommendation of ANSI/ESD S4.1) tested per ANSI/ESD S4.1 and ESD TR53. Resistance to solvents, hot solder and soldering irons makes the Ultra-R2 Dissipative Rubber Table Mat a versatile static-safe worksurface. Electrical performance is accomplished by using a two-layer combination of top color static dissipative and bottom black conductive rubber materials. Compatible with Constant Monitors. Available in rolls, mats and mats with ground cord.



Mat Item Numbers

| Size | Blue | Mat Includes: |
|-------------------------------|-------------|---|
| *24" x 48" (0.6 m x 1.2 m) | RM2448L2RBL | 1 Table Mat, size as 2 Female 3/8" Snaps |

specified s (Snaps installed on long side of mat)

*Includes 1/2" radius corners

| | Table Mat Kit Includes: | |
|---|---|--|
| | 1 Table Mat, size as specified | |
| L | 1 LPCGC151M 15' (4.6 m) Ground Cord | |
| | 2 Female 3/8" Snaps (Snaps installed on long side of mat) | |
| | | |

*Includes 1/2" radius corners

Includes roll of matting material.

United States of America



ULTRA-R2 DISSIPATIVE RUBBER TABLE MAT

PHONE (919) 718-0000

| DRAWING | DATE |
|-----------------|------|
| NUMBER | May |
| Ultra-R2 Series | 2017 |

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

SCS:

RM24600L2RBLRM30600L2RGRRM36600L2RBLRM2448L2RBL-LRM30600L2RBLRM48600L2RGRRM2436L2RGR-LRM36600L2RGRRM48600L2RBLRM2448L2RGR-LRM2436L2RBL-LRM24600L2RGRRM2448L2RBLRM2448L2RBLRM2448L2RGR-LRM2436L2RBL-LRM24600L2RGR