



used for: D-SUB COMBINATION

NOTES:

1. METALSHELLS: STEEL; min. 320µ" TIN
2. INSULATORS: PBT GF UL 94 V-0, GREEN
3. THREADED INSERT: COPPER ALLOY; min. 200µ" TIN over 80µ" NICKEL
4. COLLAR: COPPER ALLOY; min. 200µ" TIN over 80µ" NICKEL
5. MAXIMUM TORQUE VALUE FOR THREAD: 6" LBS
6. = CRITICAL DIMENSION; SPC

Directive 2002/95/EC
"RoHS"
Compliant

tolerance		2:1 (5:1)	scale:		SEE NOTES			
material:		material:		title:				
2001		date		D-SUB COMBINATION FEMALE 8W8S with threaded insert AutoCAD 2000 DIN-A 13K1A253A 3 sh: 1/1 part no: 3008W8SXX99A30X				
drawn		17.05.					name	
appd.		17.05.					Parei	
norm		E. Mickenbecker					E. Mickenbecker	
d-old							dwg no:	
rev. description		date		name				
THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GMBH DO NOT ALTER CAD DRAWING BY HAND								

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[CONEC:](#)

[3008W8SXX99A30X](#)