

Product: [9914](#) 

Low Loss 50 Ohm, RG8, 10 AWG, CMG



## Product Description

RG-8/U Type, 10 AWG solid .103" bare copper conductor, gas-injected foam HDPE insulation, Duobond® II, tinned copper braid shield (95% coverage), PVC jacket.

## Technical Specifications

### Physical Characteristics (Overall)

#### Conductor

AWG	Stranding	Material	Nominal Diameter	No. of Coax
10	Solid	BC - Bare Copper	0.103 in	1

Conductor Count:	1
------------------	---

#### Insulation

Material	Nominal Diameter
PE - Polyethylene (Foam)	0.285 in

Insulation, Table Note:	Gas Injected
-------------------------	--------------

#### Outer Shield Material

Type	Layer	Material	Material Trade Name	Coverage [%]
Tape	1	Alum / Poly / Alum	Bonded Duofoil®	100 %
Braid	2	TC - Tinned Copper		95 %

#### Outer Jacket Material

Material	Nominal Diameter
PVC - Polyvinyl Chloride	0.403 in

### Electrical Characteristics

#### Conductor DCR

Nominal Conductor DCR	Nominal Conductor DCR Conductor Resistance	Nominal Outer Shield DCR	Outer Conductor DCR
1.2 Ohm/1000ft	1.2 Ohm/1000ft	1.1 Ohm/1000ft	1.1 Ohm/1000ft

#### Capacitance

Nom. Capacitance Conductor to Shield
24.8 pF/ft

#### Inductance

Nominal Inductance
0.065 µH/ft

#### Impedance

Nominal Characteristic Impedance
50 Ohm

#### High Frequency (Nominal/Typical)

Frequency [MHz]	Nom. Insertion Loss
-----------------	---------------------

5 MHz	0.4 dB/100ft
10 MHz	0.5 dB/100ft
50 MHz	1 dB/100ft
100 MHz	1.4 dB/100ft
200 MHz	1.8 dB/100ft
400 MHz	2.6 dB/100ft
700 MHz	3.6 dB/100ft
900 MHz	4.1 dB/100ft
1000 MHz	4.4 dB/100ft
1500 MHz	5.5 dB/100ft
1800 MHz	6.1 dB/100ft
2000 MHz	6.5 dB/100ft
2500 MHz	7.5 dB/100ft
3000 MHz	8.3 dB/100ft
4000 MHz	9.9 dB/100ft

#### Delay

Nominal Delay	Nominal Velocity of Propagation (VP) [%]
1.24 ns/ft	82 %

#### Power Rating

Frequency [MHz]	Max. Power Rating [W]
5 MHz	4,021 W
10 MHz	3,217 W
50 MHz	1,609 W
100 MHz	1,149 W
200 MHz	894 W
400 MHz	619 W
700 MHz	447 W
1,000 MHz	366 W
1,500 MHz	293 W
2,000 MHz	248 W
3,000 MHz	194 W
4,000 MHz	163 W
2,500 MHz	215 W
3,000 MHz	194 W
4,000 MHz	163 W

#### Voltage

Non-UL Voltage Rating	UL Voltage Rating
300 V RMS	30 V RMS

#### VSWR

Frequency [MHz]	Max. VSWR
5-2250 MHz	1.43:1

Electrical Characteristics Notes:	30 V RMS (UL AWM Style 1354)
-----------------------------------	------------------------------

#### Temperature Range

UL Temp Rating:	80°C
Operating Temp Range:	-40°C To +80°C

#### Mechanical Characteristics

Bulk Cable Weight:	105 lbs/1000ft
Max Recommended Pulling Tension:	247 lbs
Min Bend Radius/Minor Axis:	4 in

#### Standards

NEC/(UL) Specification:	CMG
CEC/C(UL) Specification:	CMG
UL AWM Style:	UL Style 1354 (30 V 80°C)
CPR Euroclass:	Eca

RG Type:	8/U Type
----------	----------

### Applicable Environmental and Other Programs

Environmental Space:	Indoor/Outdoor
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2004-01-01
MII Order #39 (China RoHS):	Yes

### Suitability

Suitability - Aerial:	Yes
Suitability - Indoor:	Yes
Suitability - Outdoor:	Yes

### Flammability, LSOH, Toxicity Testing

UL Flammability:	UL1685 FT4 Loading
CSA Flammability:	FT4
ISO/IEC Flammability:	IEC 60332-1-2
UL voltage rating:	30 V RMS

### Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

### Part Number

#### Variants

Item #	Color	Putup Type	Length	UPC/EAN
9914.0030	Black	Reel	30 m	8719605023537
9914.00152	Black	Reel	152 m	8719605023520
9914.00305	Black	Reel	305 m	8719605023544
9914 010500	Black	Reel	500 ft	612825268901
9914 0101000	Black	Reel	1,000 ft	612825261780

Footnote:	C - CRATE REEL PUT-UP.
-----------	------------------------

### History

Update and Revision:	Revision Number: 0.289 Revision Date: 04-28-2020
----------------------	--

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Belden Wire & Cable:](#)

[9914 0101000](#) [9914 010500](#)