

Cable - CABLE-D37SUB/B/S/150/KONFEK/S - 2302214

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)

Round shielded cable set, with 37-pos. D-SUB female and male connectors, cable length: 1.5 m



The illustration shows a 15-position version



Key Commercial Data

| Packing unit | 1 pc |
|--------------------------------------|----------|
| Weight per Piece (excluding packing) | 401.0 g |
| Custom tariff number | 85444290 |
| Country of origin | Hungary |

Technical data

General

| Nominal voltage U _N | 125 V AC/DC |
|---|--|
| Max. current carrying capacity per path | 2 A |
| Max. conductor resistance | $\leq 0.09~\Omega/m$ |
| Length of cable | 1.5 m |
| Single wire, cross section | 0.25 mm ² |
| Single wire, cross section [AWG] | 24 |
| External diameter | 12.5 mm |
| Shielding | yes |
| | Tinned copper-braided shield, approx. 85% covering |
| Insertion/withdrawal cycles | > 200 |

Environmental conditions

| Ambient temperature (operation) | -20 °C 50 °C |
|---|--------------|
| Ambient temperature (storage/transport) | -20 °C 70 °C |
| Flame resistance | IEC 60332-1 |



Cable - CABLE-D37SUB/B/S/150/KONFEK/S - 2302214

Technical data

Environmental conditions

| Environmental conditions | |
|----------------------------------|-------------------------|
| | DIN VDE 0482 Part 332-1 |
| Connector, module side | |
| Connection method | D-SUB pin strip |
| Number of connections | 1 |
| Number of positions | 37 |
| Connector, controller side | |
| Connection method | D-SUB socket strip |
| Number of connections | 1 |
| Number of positions | 37 |
| Supported controller | |
| Controller | universal |
| Standards and Regulations | |
| Connection in acc. with standard | CUL |
| Flame resistance | IEC 60332-1 |
| | DIN VDE 0482 Part 332-1 |

Classifications

eCl@ss

| eCl@ss 4.0 | 27060306 |
|------------|----------|
| eCl@ss 4.1 | 27060306 |
| eCl@ss 5.0 | 27061801 |
| eCl@ss 5.1 | 27061801 |
| eCl@ss 6.0 | 27061801 |
| eCl@ss 7.0 | 27061801 |
| eCl@ss 8.0 | 27249205 |

ETIM

| ETIM 2.0 | EC000237 |
|----------|----------|
| ETIM 3.0 | EC000237 |
| ETIM 4.0 | EC000237 |
| ETIM 5.0 | EC000237 |

UNSPSC

| UNSPSC 6.01 | 26121620 |
|---------------|----------|
| UNSPSC 7.0901 | 26121620 |




Cable - CABLE-D37SUB/B/S/150/KONFEK/S - 2302214

Classifications

UNSPSC

| UNSPSC 11 | 26121620 |
|--------------|----------|
| UNSPSC 12.01 | 26121620 |
| UNSPSC 13.2 | 26121620 |

| UNSPSC 13.2 | 26121620 |
|---|----------|
| Approvals | |
| Approvals | |
| | |
| Approvals | |
| UL Recognized / cUL Recognized / CSA / EAC / EAC / cULus Recognized | |
| Ex Approvals | |
| | |
| Approvals submitted | |
| | |
| Approval details | |
| | |
| 51 | |
| UL Recognized \$1 | |
| | |
| cUL Recognized | |
| COL Necognized | |
| | |
| CSA (1) | |
| | |
| EAC | |
| EAC | |
| LAG | |
| | |





Phoenix Contact 2016 @ - all rights reserved http://www.phoenixcontact.com

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Phoenix Contact: 2302214