	REV. DATE DESCRIPTION
	NC 09/07/99 INITIAL RELEASE
	A 07/21/05 UPDATE DRAWING FORMAT
2.00 [.079] +	
6.35 HEX 6.35 HEX 6.35 IEX 1.50 [.059] 6.35 HEX 6.35 HEX 6.35 IEX 6.35 IEX 6.3	Image: state stat
S.10 [.201] 4.50 [.177] RECOMMENDED MOUNTING HOLE	(HEATSHRINK TUBE)
UNLESS OTHERWISE SPECIFIED DIMENSIONS A IN MILLINETERS. DIMENSIONS IN [] ARE IN	RE APPROVALS DATE
8 INCHES AND FOR CUSTOMER REFERANCE ON   7 HEAT SHRINK TUBE 1	DRAWN G.R.S. 07/21/05 Amphenol Connex
7 HEAT SHRINK TUBE 1 Uncess of memory according to the provided of t	
5 HEX NUT BRASS GOLD 1 8 - 30mm ± 0.40mm	PART DESCRIPTION SMB_BUILKHEAD_CRIMP_LACK
4 LOCK WASHER BRASS GOLD 1   UNLESS OTHERWISE SPECIFIED	(FOR RG-178B/U, 196A/U CABLE)
3 CONTACT PIN BRASS GOLD 1 UNLESS OTHERWISE SPECIFIED TOLERANCES FOR INCRESS ARE	SHEET 1 OF 1
2 INSULATOR TEFLON NATURAL 1 .020315 = ± 0.007'   1 DODY DDAYS .0015 .315 - 1.180 = ± 0.015'	142231
2 INSULATOR TEFLON NATURAL 1 .020315 = ± 0.007'	

## **Mouser Electronics**

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Amphenol: <u>142231</u>